

**TITLE 16****STREETS AND SIDEWALKS, ETC<sup>1</sup>****CHAPTER****1. STREETS.****CHAPTER 1****STREETS****SECTION**

16-101. Minimum requirements.

**16-101. Minimum requirements.** All new roads and/or streets in the Town of Kimball, Tennessee, before such roads or streets are accepted as public roads or streets by the town, and before the town will agree to become responsible for the maintenance and upkeep of such roads or streets, shall be constructed under the following minimum requirements:

(1) The right of way indicated for street or road purposes shall have a minimum width of at least 40 feet.

(2) Street or road must be properly graded and drained so that surface water will drain from the roadway and drainage ditches.

(3) The street or road must be graded to the full width of the right of way, except for required drainage ditches, and smoothed and compacted and all large rocks, stumps, roots, brush and other objectionable materials removed therefrom.

(4) The travelled portion of the street shall be covered with a layer of at least 4 inches of crushed stone, gravel, or other material acceptable by the board of mayor and aldermen, and shall be spread evenly and compactly for a minimum width of 20 feet.

(5) An adequate drainage system shall be provided, including necessary open ditches, and culverts or bridges of adequate size with no culvert to be less than 12 inches in diameter.

(6) The board of mayor and aldermen may under special circumstances where it appears impractical to comply with the right of way widths herein set out, accept a street with a narrower right of way width, but the reasons therefor must be set out upon the minutes of the town. (Ord. #8, April 1965)

---

<sup>1</sup>Municipal code reference

Related motor vehicle and traffic regulations: title 15.