

TITLE 18

WATER AND SEWERS¹

CHAPTER

1. SEWAGE.
2. SEWER USE ORDINANCE.
3. CROSS CONNECTIONS, AUXILIARY INTAKES, ETC.

CHAPTER 1

SEWAGE²

SECTION

- 18-101. Definitions.
- 18-102. Use of public sewers required.
- 18-103. Private sewage disposal.
- 18-104. Building sewers and connections.
- 18-105. Use of the public sewer.
- 18-106. Protection from damage.
- 18-107. Powers and authority of inspectors.
- 18-108. Violations.

18-101. Definitions. Unless the context specifically indicates otherwise, the meanings of terms used in this chapter shall be as follows:

(1) "BOD" (denoting Biochemical Oxygen Demand) shall mean the quantity of oxygen utilized in the biochemical oxidation of organic matter under standard laboratory procedure in five (5) days at 20° C., expressed in parts per million by weight.

(2) "Building drain" shall mean that part of the lowest horizontal piping of a drainage system which receives the discharge from soil, waste, and

¹Municipal code references

Building, utility and housing codes: title 12.

Refuse disposal: title 17.

²Municipal code reference

Plumbing code: title 12, chapter 2.

Ordinances amending the water and sewer rates are of record in the city recorder's office.

other drainage pipes inside the walls of the building and conveys it to the building sewer, beginning five (5) feet outside the inner face of the building wall.

(3) "Building sewer" shall mean the extension from the building drain to the public sewer or other place of disposal.

(4) "Industrial wastes" shall mean the liquid wastes from industrial manufacturing processes as distinct from sanitary sewage.

(5) "Natural outlet" shall mean any outlet into a watercourse, pond, ditch, lake, or other body of surface or ground water.

(6) "Person" shall mean any individual, firm, company, association, society, corporation, or group.

(7) "pH" shall mean the logarithm of the reciprocal of the weight of hydrogen ions in grams per liter of solution.

(8) "Public sewer" shall mean a sewer in which all owners of abutting properties have equal rights, and which is controlled by public authority.

(9) "Sewage" shall mean a combination of the water-carried wastes from residences, business buildings, institutions, and industrial establishments, together with such ground, surface, and stormwaters as may be present.

(10) "Shall" is mandatory; "may" is permissive.

(11) "Superintendent" shall mean the Superintendent of the Water Department of the Board of Public Utilities of the City of LaFollette, or his authorized deputy, agent, or representative.

(12) "Suspended solids" shall mean solids that either float on the surface of, or are in suspension in water, sewage, or other liquids, and which are removable by laboratory filtering. (1975 Code, § 8-201)

18-102. Use of public sewers required. (1) It shall be unlawful for any person to place, deposit, or permit to be deposited in any unsanitary manner on public or private property within the City of LaFollette, or in any area under the jurisdiction of said city, any human or animal excrement, garbage, or other objectionable waste.

(2) It shall be unlawful to discharge to any natural outlet within the City of LaFollette, or in any area under the jurisdiction of said city, any sanitary sewage, industrial wastes, or other polluted waters, except where suitable treatment has been provided in accordance with subsequent provisions of this chapter.

(3) Except as hereinafter provided, it shall be unlawful to construct or maintain any privy, privy vault, septic tank, cesspool, or other facility intended or used for the disposal of sewage.

(4) The owner of all houses, buildings, or properties used for human occupancy, employment, recreation, or other purposes, situated within the city, and abutting on any street, alley, or right-of-way in which there is now located

or may in the future be located a public sanitary or combined sewer of the city, is hereby required at his expense to install suitable toilet facilities therein, and to connect such facilities directly with the proper public sewer in accordance with the provisions of this chapter, within ninety (90) days after date of official notice to do so, provided that said public sewer is within one hundred (100) feet of the property line. (1975 Code, § 8-202)

18-103. Private sewage disposal. (1) Where a public sanitary sewer is not available under the provisions of § 18-102(4), the building sewer shall be connected to a private sewage disposal system. The owner shall first obtain a written permit signed by the superintendent. The application for such permit shall be made on a form furnished by the city which the applicant shall supplement by any plans, specifications, and other information as are deemed necessary by the superintendent. A permit and inspection fee of five dollars (\$5.00) shall be paid to the city treasurer at the time the application is filed.

(2) A permit for a private sewage disposal system shall not become effective until the installation is completed to the satisfaction of the superintendent. He shall be allowed to inspect the work at any stage of construction and, in any event, the applicant for the permit shall notify the superintendent when the work is ready for final inspection, and before any underground portions are covered. The inspection shall be made within forty-eight (48) hours of the receipt of notice by the superintendent.

(3) At such time as a public sewer becomes available to a property served by a private sewage disposal system as provided in § 18-102(4), a direct connection shall be made to the public sewer in compliance with this chapter, and any septic tanks, cesspools, and similar private sewage disposal facilities shall be abandoned and filled with suitable material.

(4) The owner shall operate and maintain the private sewage disposal facilities in a sanitary manner at all times, at no expense to the city.

(5) No statement contained in this section shall be construed to interfere with any additional requirements that may be imposed by the health officer. (1975 Code, § 8-203)

18-104. Building sewers and connections. (1) No unauthorized person shall uncover, make any connections with or opening into, use, alter, or disturb any public sewer or appurtenance thereof without first obtaining a written permit from the superintendent.

(2) There shall be two (2) classes of building sewer permits: (a) for residential and commercial service, and (b) for service to establishments producing industrial wastes. In either case, the owner or his agent shall make application on a special form furnished by the city. The permit application shall be supplemented by any plans, specifications, or other information considered

pertinent in the judgment of the superintendent. A permit and inspection fee of five dollars (\$5.00) for a residential or commercial building sewer permit and fifteen dollars (\$15.00) for an industrial building sewer permit shall be paid to the city treasurer at the time the application is filed.

(3) All costs and expenses incident to the installation and connection of the building sewer shall be borne by the owner. The owner shall indemnify the city from any loss or damage that may directly or indirectly be occasioned by the installation of the building sewer.

(4) A separate and independent building sewer shall be provided for every building; except where one building stands at the rear of another on an interior lot and no private sewer is available or can be constructed to the rear building through an adjoining alley, court, yard, or driveway. In such case the building sewer from the front building may be extended to the rear building and the whole considered as two building sewers.

(5) Old building sewers may be used in connection with new buildings only when they are found, on examination and test by the superintendent, to meet all requirements of this chapter.

(6) The building sewer shall be cast iron soil pipe, ASTM specification (A74), or equal; or vitrified clay sewer pipe, ASTM specification (C13) or equal. All joints shall be tight and waterproof. Building sewers shall not be placed in the same trench with water service lines. If installed in filled or unstable ground, the building sewer shall be properly bedded as approved by the superintendent.

(7) The size and slope of the building sewer shall be subject to the approval of the superintendent, but in no event shall the diameter be less than four (4) inches. The slope of such 4-inch pipe shall be not less than one-eighth (1/8) inch per foot.

(8) Whenever possible the building sewer shall be brought to the building at an elevation below the basement floor. No building sewer shall be laid parallel to or within three (3) feet of any bearing wall which might thereby be weakened. The building sewer shall be laid at uniform grade and in straight alignment in so far as possible. Changes in direction shall be made only with properly curved pipe and fittings.

(9) All excavations required for the installation of a building sewer shall be open trench work unless otherwise approved by the superintendent. Pipe laying and backfill shall be performed in accordance with ASTM specification (C12) except that no backfill shall be placed until the work has been inspected.

(10) All joints and connections shall be made gastight and watertight. Cast iron pipe joints shall be firmly packed with oakum or hemp and filled with molten lead, Federal Specification (QQ-L-156), not less than one (1) inch deep. Lead shall be run in one pouring and calked tight. No paint,

varnish, or other coatings shall be permitted on the jointing material until after the joint has been tested and approved.

All joints in vitrified clay pipe shall be:

- (a) Factory made joints of materials having resilient properties as specified in ASTM 425;
- (b) Approved hot-poured joints;
- (c) Bituminous joints; or
- (d) Other acceptable joints.

All hot-poured joints shall be made in strict accordance with the manufacturer's instructions, using suitable recommended primers whenever the hazard of wet surfaces exists. All surfaces of the joint shall be cleaned and dried before pouring or each joint shall be poured completely in one operation.

The hot-poured compounds used in jointing clay sewer pipes shall have a bond strength of not less than 100 psi when poured against a dry clay surface. These compounds shall be non-porous, non-absorbent and not subject to bacterial or chemical action.

The finished joint shall not soften so as to destroy its effectiveness when subjected to temperatures of 160° F. and shall be chemically inert to wastes carried by the drainage system. Joints shall not be tested until one hour after pouring.

Sulfur compounds are subject to bacterial attack and shall not be used. Cement mortar joints can be corroded by sewage and soil acids and are not recommended for use.

All jointing materials and methods to be used shall be approved by the superintendent.

(11) The connection of the building sewer into the public sewer shall be made at the "Y" branch, if such branch is available at a suitable location. If the public sewer is twelve (12) inches in diameter or less, and no properly located "Y" branch in the public sewer at the location specified by the superintendent. Where the public sewer is greater than twelve (12) inches in diameter, and no "Y" branch is available a neat hole may be cut into the street sewer to receive the building sewer, with entry in the downstream direction at proper angle. The correct clay fitting shall be used to make such connection, with the spigot end cut so as not to extend past the inner surface of the public sewer. The invert of the building sewer at the point of connection shall be at the same or at a higher elevation than the invert of the public sewer. A smooth, neat joint shall be made, and the connection made secure and water-tight by encasement in concrete. Special fittings may be used for the connection only when approved by the superintendent.

(12) The applicant for the building sewer permit shall notify the superintendent when the building sewer is ready for inspection and connection

to the public sewer. The connection shall be made under the supervision of the superintendent or his representative.

(13) All excavations for building sewer installation shall be adequately guarded with barricades and lights so as to protect the public from hazard. Streets, sidewalks, parkways and other public property disturbed in the course of the work shall be restored in a manner satisfactory to the city. (1975 Code, § 8-204)

18-105. Use of the public sewer. (1) No person shall discharge or cause to be discharged any stormwater, surface water, ground water, roof runoff, subsurface drainage, cooling water, or unpolluted industrial process waters to any sanitary sewer.

(2) Stormwater and all other unpolluted drainage shall not be discharged to sanitary sewers. Industrial cooling water or unpolluted process waters may be discharged, upon approval of the superintendent, to a storm sewer, or natural outlet.

(3) Except as hereinafter provided, no person shall discharge or cause to be discharged any of the following described waters or wastes to any public sewer:

(a) Any liquid or vapor having a temperature higher than one hundred and fifty degrees (150°)F.

(b) Any water or waste which may contain more than 100 parts per million by weight, of fat, oil, or grease.

(c) Any gasoline, benzene, naphtha, fuel oil, or other flammable or explosive liquid solid or gas.

(d) Any garbage that has not been properly shredded.

(e) Any ashes, cinders, sand, mud, straw, shavings, metal, glass, rags, feathers, tar, plastics, wood, paunch manure, or any other solid or viscous substance capable of causing obstruction to the flow in sewers or other interference with the proper operation of the sewage works.

(f) Any waters or wastes having a pH lower than 5.5 or higher than 9.0, or having any other corrosive property capable of causing damage or hazard to structures, equipment, and personnel of the sewage works.

(g) Any waters or wastes containing a toxic or poisonous substance in sufficient quantity to injure or interfere with any sewage treatment process, constitute a hazard to humans or animals, or create any hazard in the receiving waters of the sewage treatment plant.

(h) Any waters or wastes containing suspended solids of such character and quantity that unusual attention or expense is required to handle such materials at the sewage treatment plant.

(i) Any noxious or malodorous gas or substance capable of creating a public nuisance.

(4) Grease, oil, and sand interceptors shall be provided when, in the opinion of the superintendent, they are necessary for the proper handling of liquid wastes containing grease in excessive amounts, or any flammable wastes, sand, and other harmful ingredients; except that such interceptors shall not be required for private living quarters or dwelling units. All interceptors shall be of a type and capacity approved by the superintendent and shall be so located as to be readily and easily accessible for cleaning and inspection.

Grease and oil interceptors shall be constructed of impervious materials capable of withstanding abrupt and extreme changes in temperature. They shall be of substantial construction, watertight, and equipped with easily removable covers which when bolted in place shall be gastight and watertight.

(5) Where installed, all grease, oil, and sand interceptors shall be maintained by the owner, at his expense, in continuously efficient operation at all times.

(6) The admission into the public sewers of any waters or wastes having:

(a) A 5-day Biochemical Oxygen Demand greater than (300) parts per million by weight; or

(b) Containing more than (350) parts per million by weight of suspended solids; or

(c) Containing any quantity of substances having the characteristics described in subsection (3) above; or

(d) Having an average daily flow greater than 2% of the average daily sewage flow of the city, shall be subject to the review and approval of the superintendent. Where necessary in the opinion of the superintendent, the owner shall provide, at his expense such preliminary treatment as may be necessary to:

(i) Reduce the Biochemical Oxygen Demand to (300) parts per million and the suspended solids to (350) parts per million by weight; or

(ii) Reduce the objectionable characteristic or constituents to within the maximum limits provided for in subsection (3) above; or

(iii) Control the quantities and rates of discharge of such waters or wastes. Plans, specifications, and any other pertinent information relating to proposed preliminary treatment facilities shall be submitted for the approval of the superintendent and of the Water Pollution Control Commission of the State of Tennessee, and no construction of such facilities shall be commenced until said approvals are obtained in writing.

(7) Where preliminary treatment facilities are provided for any waters of wastes, they shall be maintained continuously in satisfactory and effective operation by the owner at his expense.

(8) When required by the superintendent, the owner of any property served by a building sewer carrying industrial wastes shall install a suitable control manhole in the building sewer to facilitate observation, sampling, and measurement of the wastes. Such manhole, when required, shall be accessibly and safely located, and shall be constructed in accordance with plans approved by the superintendent. The manhole shall be installed by the owner at his expense and shall be maintained by him so as to be safe and accessible at all times.

(9) All measurements, tests, and analyses of the characteristics of waters and wastes to which reference is made in subsections (3) and (6) above shall be determined in accordance with "Standard Methods for the Examination of Water and Sewage," and shall be determined at the control manhole provided for in subsection (8), or upon suitable samples taken at said control manhole. In the event that no special manhole has been required, the control manhole shall be considered to be the nearest downstream manhole in the public sewer to the point at which the building sewer is connected.

(10) No statement contained in this section shall be construed as preventing any special agreement or arrangement between the city and any industrial concern whereby an industrial waste of unusual strength or character may be accepted by the city for treatment, subject to payment therefor by the industrial concern. (1975 Code, § 8-205)

18-106. Protection from damage. No unauthorized person shall maliciously, willfully, or negligently break, damage, destroy, uncover, deface, or tamper with any structure, appurtenance, or equipment which is a part of the city sewage works. Any person violating this provision shall be subject to immediate arrest under charge of disorderly conduct. (1975 Code, § 8-206)

18-107. Powers and authority of inspectors. The superintendent and other duly authorized employees of the city bearing proper credentials and identification shall be permitted to enter all properties for the purposes of inspection, observation, measurement, sampling, and testing in accordance with the provisions of this chapter. (1975 Code, § 8-207)

18-108. Violations. (1) Any person found to be violating any provision of this chapter except § 18-106 shall be served by the city with a written notice stating the nature of the violation and providing a reasonable time limit for the satisfactory correction thereof. The offender shall, within the period of time stated in such notice, permanently cease all violations.

(2) Any person who shall continue any violation beyond the time limit provided for in the preceding subsection shall be guilty of a misdemeanor, and on conviction thereof may be fined under the general penalty clause for this code.

(3) Any person violating any of the provisions of this chapter shall become liable to the city for any expense, loss, or damage occasioned the city by reason of such violation. (1975 Code, § 8-208)

CHAPTER 2**SEWER USE ORDINANCE****SECTION**

- 18-201. Purpose and policy.
- 18-202. Definitions.
- 18-203. Abbreviations.
- 18-204. Connection to public sewers.
- 18-205. Private sewage disposal.
- 18-206. Discharge regulations.
- 18-207. Fees.
- 18-208. Administration.
- 18-209. Enforcement.
- 18-210. Penalty: costs.
- 18-211. Protection from damage.
- 18-212. Powers and authority of inspectors.

18-201. Purpose and policy. This chapter sets forth uniform requirements for direct and indirect contributors into the wastewater collection and treatment system for the City of LaFollette and enables the city to comply with all applicable state and federal laws required by the Clean Water Act of 1977 and the General Pretreatment Regulations (40 CFR, Part 403).

The objectives of this chapter are:

- (1) To prevent the introduction of pollutants into the municipality wastewater system which will interfere with the operation of the system or contaminate the resulting sludge;
- (2) To prevent the introduction of pollutants into the municipal wastewater system which will pass through the system, inadequately treated, into receiving waters or the atmosphere or otherwise be incompatible with the system;
- (3) To improve the opportunity to recycle and reclaim wastewaters and sludges from the system; and
- (4) To provide for equitable distribution of the cost of the municipal wastewater system.

This chapter provides for the regulation of direct and indirect contributors to the municipal wastewater system through the issuance of permits to certain non-domestic users and through enforcement of general requirements for the other users, authorizes monitoring and enforcement activities, requires user reporting, assumes that existing customers' capacity will not be preempted, and provides for the setting of fees for the equitable distribution of costs resulting from the program established herein.

This chapter shall apply to the City of LaFollette and to persons outside the city who are, by contract or agreement with the city, users of the city POTW. This chapter supersedes Ordinance #317 and #504. Except as otherwise provided herein, the superintendent of the city POTW shall administer, implement, and enforce the provisions of this chapter. Any conflicts between this chapter and any prior ordinance shall be controlled by the language of this chapter. (Ord. #514, May 1988)

18-202. Definitions. Unless the context specifically indicates otherwise, the following terms and phrases, as used in this chapter, shall have the meanings hereinafter designated:

(1) "Act" or "the Act." The Federal Water Pollution Control Act, also known as the Clean Water Act, as amended, 33 U.S.C. 1251, et. seq.

(2) "Approval authority." The director in an NPDES state with an approved state pretreatment program and the administrator of the EPA in a non-NPDES state without an approved state pretreatment program.

(3) "Authorized representative of industrial user." An authorized representative of an industrial user may be:

(a) A principal executive officer of at least the level of vice-president, if the industrial user is a corporation;

(b) A general partner or proprietor if the industrial user is a partnership or proprietorship, respectively;

(c) A duly authorized representative of the individual designated above if such representative is responsible for the overall operation of the facilities from which the indirect discharge originates.

(4) "Biochemical Oxygen Demand (BOD)." The quantity of oxygen utilized in the biochemical oxidation of organic matter under standard laboratory procedure, five (5) days at 20° centigrade expressed in terms of weight and concentration (milligrams per liter (mg/l)).

(5) "Building drain." That part of the lowest horizontal piping of a drainage system which receives the discharge from soil, waste, and other drainage pipes inside the walls of the building and conveys it to the building sewer, beginning 5 feet outside the inner face of the building wall.

(6) "Building sewer." The extension from the building drain to the public sewer or other place of disposal.

(7) "Categorical standards." National categorical pretreatment standards or pretreatment standard.

(8) "City." The City of LaFollette or the City Council, City of LaFollette, Tennessee.

(9) "Compatible pollutant." Shall mean BOD, suspended solids, pH, and fecal coliform bacteria, and such additional pollutants as are now or may be in the future specified and controlled in this city's NPDES permit for its

wastewater treatment works where sewer works have been designed and used to reduce or remove such pollutants.

(10) "Cooling water." The water discharged from any use such as air conditioning, cooling or refrigeration, or to which the only pollutant added is heat.

(11) "Control authority." The term "control authority" shall refer to the "approval authority," defined hereinabove; or the superintendent if the city has an approved pretreatment program under the provisions of 40 CFR, 403.11.

(12) "Customer." Means any individual, partnership, corporation, association, or group who receives sewer service from the city under either an expressed or implied contract requiring payment to the city for such service.

(13) "Direct discharge." The discharge of treated or untreated wastewater directly to the waters of the State of Tennessee.

(14) "Domestic wastewater." Wastewater that is generated by a single family, apartment or other dwelling unit or dwelling unit equivalent containing sanitary facilities for the disposal of wastewater and used for residential purposes only.

(15) "Environmental Protection Agency." The U.S. Environmental Protection Agency, or where appropriate the term may also be used as a designation for the administrator or other duly authorized official of said agency.

(16) "Garbage." Shall mean solid wastes from the domestic and commercial preparation, cooking, and dispensing of food, and from the handling, storage, and sale of produce.

(17) "Grab sample." A sample which is taken from a waste stream on a one-time basis with no regard to the flow in the waste stream and without consideration of time.

(18) "Holding tank waste." Any waste from holding tanks such as vessels, chemical toilets, campers, trailers, septic tanks, and vacuum-pump tank trucks.

(19) "Incompatible pollutant." Shall mean any pollutant which is not a "compatible pollutant" as defined in this section.

(20) "Indirect discharge." The discharge or the introduction of non-domestic pollutants from any source regulated under Section 307(b) or (c) of the Act, (33 U.S.C. 1317), into the POTW (including holding tank waste discharged into the system).

(21) "Industrial user." A source of indirect discharge which does not constitute a "discharge of pollutants" under regulations issued pursuant to Section 402, of the Act (33 U.S.C. 1342).

(22) "Industrial waste." Shall mean the liquid wastes from industrial processes as distinct from sanitary sewage.

(23) "Interference." The inhibition or disruption of the municipal wastewater treatment processes or operations which contributes to a violation of any requirement of the city's NPDES permit. The term includes prevention of sewage sludge use or disposal by the POTW in accordance with 405 of Act, (33 U.S.C. 1345) or any criteria, guidelines, or regulations developed pursuant to the Solid Waste Disposal Act (SWDA), the Clean Air Act, the Toxic Substances Control Act, or more stringent state criteria (including those contained in any State sludge management plan prepared pursuant to Title IV of SWDA) applicable to the method of disposal or use employed by the municipal wastewater treatment system.

(24) "National Categorical Pretreatment Standard or Pretreatment Standard." Any regulation containing pollutant discharge limits promulgated by the EPA in accordance with Section 307(b) and (c) of the Act (33 U.S.C. 1347) which applies to a specific category of industrial users.

(25) "Natural outlet." Shall mean any outlet into a watercourse, pond, ditch, lake, or other body of surface or ground water.

(26) "NPDES (Natural Pollutant Discharge Elimination System)." Shall mean the program for issuing, conditioning, and denying permits for the discharge of pollutants from point sources into navigable waters, the contiguous zone, and the oceans pursuant to Section 402 of the Federal Water Pollution Control Act as amended.

(27) "New source." Any source, the construction of which is commenced after the publication of proposed regulations prescribing a Section 307(c) (33 U.S.C. 1317) categorical pretreatment standard which will be applicable to such source, if such standard is thereafter promulgated within 120 days of proposal in the federal register. Where the standard is promulgated later than 120 days after proposal, a new source means any source, the construction of which is commenced after the date of promulgation of the standard.

(28) "Person." Any individual, partnership, co-partnership, firm, company, corporation, association, joint stock company, trust, estate, governmental entity or any other legal entity, or their legal representatives, agents or assigns. The masculine gender shall include the feminine, the singular shall include the plural where indicated by the context.

(29) "pH." The logarithm (base 10) of the reciprocal of the concentration of hydrogen ions expressed in grams per liter of solution.

(30) "Pollution." The man-made or man-induced alteration of the chemical, physical, biological, and radiological integrity of water.

(31) "Pollutant." Any dredged spoil, solid waste, incinerator residue, sewage, garbage, sewage sludge, munitions, chemical substances, biological materials, radioactive materials, heat, wrecked or discharged equipment, rock, sand, cellar dirt and industrial, municipal, and agricultural waste discharged into water.

(32) "Pretreatment or treatment." The reduction of the amount of pollutants, the elimination of pollutants, or the alternation of the nature of pollutant properties in wastewater to a less harmful state prior to or in lieu of discharging or otherwise introducing such pollutants into a POTW. The reduction or alteration can be obtained by physical, chemical, or biological processes, or process changes other means, except as prohibited by 40 CFR Section 40.36(d).

(33) "Pretreatment requirements." Any substantive or procedure requirement related to pretreatment, other than a national pretreatment standard imposed on an industrial user.

(34) "Publicly Owned Treatment Works (POTW)." A treatment works as defined by Section 212 of the Act, (33 U.S.C. 1292) which is owned in this instance by the city. This definition includes any sewers that convey wastewater to the POTW treatment plant, but does not include pipes, sewers or other conveyances not connected to a facility providing treatment. For the purposes of this chapter, "POTW" shall also include any sewers that convey wastewaters to the POTW from persons outside the city who are, by contract or agreement with the city, users of the city's POTW.

(35) "Public sewer." Shall mean a sewer in which all owners of abutting properties have equal rights, and is controlled by public authority.

(36) "POTW treatment plant." That portion of the POTW designed to provide treatment to wastewater.

(37) "Shall" is mandatory; "May" is permissive.

(38) "Sewage." Shall mean a combination of the water-carried wastes from residences, business buildings, institutions, and industrial establishments, together with such ground, surface, and storm waters as may be present.

(39) "Slug." Shall mean any discharge of water, sewage, or industrial waste which in concentration of any given constituent or in quantity of flow exceeds for any period of duration longer than fifteen (15) minutes more than five (5) times the average twenty-four (24) hour concentrations of flows during normal operation or any discharge of whatever duration that causes the sewer to overflow or back up in an objectionable way or any discharge of whatever duration that interferes with the proper operation of the wastewater treatment facilities or pumping stations.

(40) "State." State of Tennessee.

(41) "Standard Industrial Classification (SIC)." A classification pursuant to the Standard Industrial Classification Manual issued by the Executive Office of the President, Office of Management and Budget, 1972.

(42) "Storm water." Any flow occurring during or following any form of natural precipitation and resulting therefrom.

(43) "Storm sewer or storm drain." Shall mean a pipe or conduit which carries storm and surface waters and drainage, but excludes sewage and

industrial wastes; it may, however, carry cooling waters and unpolluted waters, upon approval of the superintendent.

(44) "Suspended solids." The total suspended matter that floats on the surface of, or is suspended in, water, wastewater or other liquids, and which is removable by laboratory filtering.

(45) "Superintendent." Shall mean the superintendent of the water department of the Board of Public Utilities of the City of LaFollette, or his authorized deputy, agent, or representative.

(46) "Toxic pollutant." Any pollutant or combination of pollutants listed as toxic in regulations promulgated by the Administrator of the Environmental Protection Agency under the provision of CWA (307 (a)) or other Acts.

(47) "Twenty-Four (24) Hour Flow Proportional Composite Sample." A sample consisting of several sample portions collected during a 24-hour period in which the portions of a sample are proportioned to the flow and combined to form a representative sample.

(48) "User." Any person who contributes, causes or permits the contribution of wastewater into the city's POTW.

(49) "Wastewater." The liquid and water-carried industrial or domestic wastes from dwellings, commercial buildings, industrial facilities, and institutions, whether treated or untreated, which is contributed into or permitted to enter the POTW.

(50) "Wastewater treatment systems." Defined the same as POTW.

(51) "Waters of the state." All streams, lakes, ponds, marshes, watercourses, waterways, wells, springs, reservoirs, aquifers, irrigation systems, drainage systems and all other bodies or accumulations of water, surface or underground, natural or artificial, public or private, which are contained within, flow through or border upon the state or any portion thereof. (Ord. #514, May 1988)

18-203. Abbreviations. The following abbreviations shall have the designated meanings:

BOD	-	Biochemical Oxygen Demand
CFR	-	Code of Federal Regulations
COD	-	Chemical Oxygen Demand
EPA	-	Environmental Protection Agency
l	-	Liter
mg	-	Milligrams
mg/l	-	Milligrams per liter
NPDES	-	National Pollutant Discharge Elimination System
POTW	-	Publicly Owned Treatment Works
SIC	-	Standard Industrial Classification
SWDA	-	Solid Waste Disposal Act, 42 U.S.C. 6901, et.seq.

TSS - Total Suspended Solids
 USC - United States Code

(Ord. #514, May 1988)

18-204. Connection to public sewers. (1) Requirements for proper wastewater disposal. (a) It shall be unlawful for any person to place, deposit, or permit to be deposited in an unsanitary manner upon public or private property within the City of LaFollette, or in any area under the jurisdiction of said city, any human or animal excrement, garbage, or other objectionable waste.

(b) It shall be unlawful to discharge to any natural outlet within the City of LaFollette, or in any area under the jurisdiction of said city, any sanitary sewage, industrial wastes, or other polluted waters, except where suitable treatment has been provided in accordance with subsequent provisions of this chapter.

(c) Except as hereinafter provided, it shall be unlawful to construct or maintain any privy, privy vault, septic tank, cesspool, or other facility intended or used for the disposal of sewage.

(d) The owner of all houses, buildings or properties used for human occupancy, employment, recreation, or other purpose, situated within the city and abutting on any street, alley or right-of-way in which there is now located or may in the future be located a public sanitary or combined sewer of the city, is hereby required at his expense to install suitable toilet facilities therein, and to connect such facilities directly with the proper public sewer in accordance with the provisions of this chapter, within ninety (90) days after date of official notice to do so, provided that said public sewer is within one hundred (100) feet of the property line.

(2) Building sewers and connections. (a) No unauthorized person shall uncover, make any connections with or opening into, use, alter or disturb any public sewer or appurtenance thereof without first obtaining a written permit from the superintendent.

(b) There shall be two (2) classes of building sewer permits:

(i) For residential and commercial service; and

(ii) For service to establishments producing industrial wastes.

In either case, the owner or his agent shall make application on a special form furnished by the LaFollette Waterworks. The permit shall be supplemented by plans, specifications, or other information deemed necessary by the LaFollette Waterworks.

(c) All costs and expense incident to the installation and connection of the building sewer shall be borne by the owner. The owner

shall indemnify the city from any loss or damage that may directly or indirectly be occasioned by the installation of the building sewer.

(d) A separate and independent building sewer shall be provided for every building; except where one building stands at the rear of another on an interior lot and no private sewer is available or can be constructed to the rear building through an adjoining alley, court, yard, or driveway, the building sewer from the front building may be extended to the rear building and the whole considered as two building sewers.

(e) Old building sewers may be used in connection with new buildings only when they are found, on examination and test by the superintendent, to meet all requirements of this chapter.

(f) The building sewer shall be cast iron soil pipe; vitrified clay sewer pipe; polyvinyl chloride pipe with solvent welded or with rubber compression joints; or such other materials of equal or superior quality as may be approved by the superintendent. All joints shall be tight and waterproof. Building sewers shall not be placed in the same trench with water service lines. If installed in filled or unstable ground, the building sewer shall be properly bedded as approved by the superintendent.

(g) The size and slope of the building sewer shall be subject to the approval of the superintendent, but in no event shall the diameter be less than four (4) inches. The slope of such 4-inch pipe shall be not less than one-eighth (1/8) inch per foot.

(h) Whenever possible the building sewer shall be brought to the building at an elevation below the basement floor. No building sewer shall be laid parallel to or within three (3) feet of any bearing wall, which might thereby be weakened. The building sewer shall be laid at uniform grade and in straight alignment insofar as possible. Changes in direction shall be made only with properly curved pipe and fittings.

(i) All excavations required for the installation of a building sewer shall be open trench work unless otherwise approved by the superintendent. Pipe laying and backfill shall be performed in accordance with ASTM Specification (C12) except that no backfill shall be placed until the work has been inspected.

(j) All joints and connections shall be made gastight and watertight.

(i) Cast iron pipe joints shall be firmly packed with oakum or hemp and filled with molten lead, Federal Specification (QQ-L-156), not less than one (1) inch deep. Lead shall be run in one pouring and caulked tight. No paint, varnish, or other coating shall be permitted on the jointing material until after the joint has been tested and approved.

(ii) All joints in vitrified clay pipe shall be:

- (A) Factory made joints of materials having resilient properties as specified in ASTM 425;
- (B) Approved hot-pour joints;
- (C) Bituminous joints; or
- (D) Other acceptable joints.

(iii) All hot-poured joints shall be made in strict accordance with the manufacturer's instructions, using suitable recommended primers whenever the hazard of wet surfaces exists. All surfaces of the joint shall be cleaned and dried before pouring, or each joint shall be poured completely in one operation.

(iv) The hot-poured compounds used in jointing clay sewer pipes shall have a bond strength of not less than 100 psi when poured against a dry clay surface. These compounds shall be non-porous, non-absorbent and not subject to bacterial or chemical action.

(v) The finished joint shall not soften so as to destroy its effectiveness when subjected to temperatures of 160° F. and shall be chemically inert to wastes carried by the drainage system. Joints shall not be tested until one hour after pouring.

(vi) Sulfur compounds are subject to bacterial attack and shall not be used. Cement mortar joints can be corroded by sewage and soil acids and are not recommended for use.

(vii) All jointing materials and methods to be used shall be approved by the superintendent.

(k) The connection of the building sewer into the public sewer shall be made at the "Y" branch, if such branch is available at a suitable location. If the public sewer is twelve (12) inches in diameter or less, and no properly located "Y" branch in the public sewer at the location specified by the superintendent. Where the public sewer is greater than twelve (12) inches in diameter, and no "Y" branch is available, a neat hole may be cut into the street sewer to receive the building sewer, with entry in the downstream direction at proper angle. The correct clay fitting shall be used to make such connection, with the spigot end cut so as not to extend past the inner surface of the public sewer. The invert of the building sewer at the point of connection shall be at the same or at a higher elevation than the invert of the public sewer. A smooth, neat joint shall be made, and the connection made secure and watertight by encasement in concrete. Special fittings may be used for the connection only when approved by the superintendent.

(l) The application for the building sewer permit shall notify the superintendent when the building sewer is ready for inspection and

connection to the public sewer. The connection shall be made under the supervision of the superintendent or his representative.

(m) All excavations for building sewer installation shall be adequately guarded with barricades and lights so as to protect the public from hazard. Streets, sidewalks, parkways and other public property disturbed in the course of the work shall be restored in a manner satisfactory to the city. (Ord. #514, May 1988)

18-205. Private sewage disposal. (1) Availability. Where a public sanitary sewer is not available under the provisions of § 18-204, the building sewer shall be connected to a private sewage disposal system. The owner shall first obtain a written permit signed by the superintendent. The application for such permit shall be made on a form furnished by the city, which the applicant shall supplement by any plans, specifications and other information as are deemed necessary by the superintendent. A permit and inspection fee of five dollars (\$5.00) shall be paid to the city treasurer at the time the application is filed.

(2) Requirements. (a) A permit for a private sewage disposal system shall not become effective until the installation is completed to the satisfaction of the superintendent. He shall be allowed to inspect the work at any stage of construction and, in any event, the applicant for the permit shall notify the superintendent when the work is ready for final inspection, and before any underground portions are covered. The inspection shall be made within forty-eight (48) hours of the receipt of notice by the superintendent.

(b) At such time as a public sewer becomes available to a property served by a private sewage disposal system as provided in § 18-204(1)(d), a direct connection shall be made to the public sewer in compliance with this chapter, and any septic tanks, cesspools, and similar private sewage disposal facilities shall be abandoned and filled with suitable material.

(c) The owner shall operate and maintain the private sewage disposal facilities in a sanitary manner at all times, at no expense to the city.

(d) No statement contained in this chapter shall be construed to interfere with any additional requirements that may be imposed by the Department of Health of the State of Tennessee and the County Health Department. No septic tank or cesspool shall be permitted to discharge to any natural outlet. (Ord. #514, May 1988)

18-206. Discharge regulations. (1) General discharge prohibitions.

(a) No user shall contribute or cause to be contributed, directly or indirectly, any pollutant or wastewater which will interfere with the operation or performance of the POTW. These general prohibitions apply to all such users of POTW whether or not the user is subject to national categorical pretreatment standards or any other national, state or local pretreatment standards or requirements. A user may not contribute the following substances to any POTW:

(i) Any liquids, solids, or gases which by reason of their nature or quantity are, or may be, sufficient either alone or by interaction with other substances to cause fire or explosion or be injurious in any other way to the POTW or to the operation of the POTW. At no time shall two successive readings on an explosion hazard meter, at the point of discharge into the system (or at any point in the system) be more than five percent (5%) nor any single reading over ten percent (10%) of the Lower Explosive Limit (LEL) of the meter. Prohibited materials include, but are not limited to, gasoline, kerosene, naphtha, benzene, toluene, xylene, ethers, alcohols, ketones, aldehydes, peroxides, chlorates, perchlorates, bromates, carbides, hydrides and sulfides and any other substances which the city, the state or EPA has notified the user is a fire hazard or a hazard to the system.

(ii) Solid or viscous substances which may cause obstruction to the flow in a sewer or other interference with the operation of the wastewater treatment facilities such as, but not limited to: grease, garbage which has not been properly shredded, animal guts or tissues, paunch manure, bones, hair, hides or fleshings, entrails, whole blood, feathers, ashes, cinders, and, spent lime, stone or marble dust, metal, glass, straw shavings, grass clippings, rags, spent grains, spent hops, waste paper, wood, plastics, gas, tar, asphalt residues, residues from refining, or processing of fuel or lubricating oil, mud, or glass grinding or polishing wastes.

(iii) Any wastewater having a pH less than 5.0 or higher than 9.0, unless the POTW is specifically designed to accommodate such wastewater, or wastewater having any other corrosive property capable of causing damage or hazard to structures, equipment, and/or personnel of the POTW.

(iv) Any wastewater containing toxic pollutants in sufficient quantity, either singly or by interaction with other pollutants, to injure or interfere with any wastewater treatment process, constitute a hazard to humans or animals, create a toxic effect in the receiving waters of the POTW, or to exceed the

limitation set forth in a categorical pretreatment standard. A toxic pollutant shall include but not be limited to any pollutant identified pursuant to Section 307(a) of the Act.

(v) Any noxious or malodorous liquids, gases, or solids which either singly or by interaction with other wastes are sufficient to create a public nuisance or hazard to life or are sufficient to prevent entry into the sewers for maintenance and repair.

(vi) Any substance which may cause the POTW effluent or any other product of the POTW such as residues, sludges, or scums, to be unsuitable for reclamation and reuse or to interfere with the reclamation process. In no case shall a substance discharged to the POTW cause the POTW to be in non-compliance with sludge use or disposal criteria, guidelines or regulations developed under Section 405 of the Act; any criteria, guidelines, or regulations affecting sludge use or disposal developed pursuant to the Solid Waste Disposal Act, the Clean Air Act, the Toxic Substances Control Act, or state criteria applicable to the sludge management method being used.

(vii) Any substance which will cause the POTW to violate its NPDES and/or state disposal system permit or the receiving water quality standards.

(viii) Any wastewater with objectionable color not removed in the treatment process, such as, but not limited to dye wastes and vegetable tanning solutions.

(ix) Any wastewater having a temperature which will inhibit biological activity in the POTW treatment plant resulting in interference, but in no case wastewater with a temperature at the introduction into the POTW which exceeds 40° C (104° F) unless the POTW treatment plant is designed to accommodate such temperature.

(x) Any pollutants, including oxygen demanding pollutants (BOD, etc.) released at a flow rate and/or pollutant concentration which a user knows or has reason to know will cause interference to the POTW. In no case shall a slug load have a flow rate or contain concentration or qualities of pollutants that exceed for any time period longer than fifteen (15) minutes more than five (5) times the average twenty-four (24) hour concentration, quantities, or flow during normal operation.

(xi) Any wastewater containing any radioactive wastes or isotopes of such half-life or concentration as may exceed limits

established by the superintendent in compliance with applicable state or federal regulations.

(xii) Any wastewater which causes a hazard to human life or creates a public nuisance.

(xiii) No person shall discharge or cause to be discharged any storm water, surface water, ground water, roof runoff, subsurface drainage, cooling water or unpolluted industrial process waters to any sanitary sewer.

(xiv) Storm water and all other unpolluted drainage shall not be discharged to sanitary sewers. Industrial cooling water or unpolluted process waters may be discharged, upon approval of the superintendent, to a storm sewer or natural outlet.

When the superintendent determines that a user(s) is contributing to the POTW, any of the above enumerated substances in such amounts as to interfere with the operation of the POTW, the superintendent shall:

(A) Advise the user(s) of the impact of the contribution on the POTW; and

(B) Develop effluent limitations for such user to correct the interference with the POTW.

(b) Grease, oil, and sand interceptors shall be provided when, in the opinion of the superintendent, they are necessary for the proper handling of liquid wastes containing grease in excessive amounts, or any flammable wastes, sand, and other harmful ingredients; except that such interceptors shall not be required for private living quarters or dwelling units. All interceptors shall be of a type and capacity approved by the superintendent, and shall be located as to be readily and easily accessible for cleaning and inspection. Grease and oil interceptors shall be constructed of impervious materials capable of withstanding abrupt and extreme changes in temperature. They shall be of substantial construction, watertight, and equipped with easily removable covers which, when bolted in place, shall be gastight and watertight.

(c) Where installed, all grease, oil and sand interceptors shall be maintained by the owner, at his expense, in continuously efficient operation at all times.

(d) The admission into the public sewers of any waters or wastes having any of the following shall be subject to the review and approval of the superintendent.

(i) A 5-day Biochemical Oxygen Demand greater than 300 parts per million by weight;

(ii) Containing more than 350 parts per million by weight of suspended solids;

(iii) Containing any quantity of substances having the characteristics described in § 18-206(1)(a);

(iv) Having an average daily flow greater than 2% of the average daily sewage flow of the city.

Where necessary in the opinion of the superintendent, the owner shall provide at his expense such preliminary treatment as may be necessary to:

(A) Reduce the Biochemical Oxygen Demand to 300 parts per million and the suspended solids to 350 parts per million by weight; or

(B) Reduce objectionable characteristics or constituents to within the maximum limits provided for in § 18-206(1)(a); or

(C) Control the quantities and rates of discharge of such waters or wastes.

Plans, specifications, and any other pertinent information relating to proposed preliminary treatment facilities shall be submitted for the approval of the superintendent and of the State of Tennessee, and no construction of such facilities shall be commenced until said approvals are obtained in writing.

(e) Each individual property owner or use of the publicly owned treatment works shall maintain or, if necessary, replace the service line, as deemed necessary by the LaFollette Water Department, to insure the line is watertight, hence preventing the inflow of rainwater, surface water, or other ground water from entering the public sewer. The expenses for said maintenance shall be that of the property owner or user.

(2) Federal categorical pretreatment standards. Upon the promulgation of the federal categorical pretreatment standards for a particular industrial subcategory, the federal standard, if more stringent than limitations imposed under this chapter for sources in that subcategory, shall immediately supersede the limitations imposed under this chapter. The superintendent shall notify all affected users of the applicable reporting requirements under 40 CFR, Section 403.12.

(3) Modification of federal categorical pretreatment standards. Where the city's wastewater treatment system achieves consistent removal of pollutants limited by federal pretreatment standards, the city may apply to the approval authority for modification of specific limits in the federal pretreatment standards. "Consistent removal" shall mean reduction in the amount of a pollutant or alteration of the nature of the pollutant by the wastewater treatment system to a less toxic or harmless state in the effluent which is achieved by the system 95 percent of the samples taken when measured

according to the procedure set forth in Section 403.7(c)(2) of (Title 40 of the Code of Federal Regulations, Part 403) - "General Pretreatment Regulations for Existing and New Sources of Pollution" promulgated pursuant to the Act. The city may then modify pollutant discharge limits in the federal pretreatment standards if the requirements contained in 40 CFR, Part 403, Section 403.7, are fulfilled and prior approval from the approval authority is obtained.

(4) Specific pollutant limitations. The influent limits acceptable for the POTW are:

Cadmium	0.002 mg/l
Chromium	0.16 mg/l
Copper	0.18 mg/l
Lead	0.13 mg/l
Mercury	0.003 mg/l
Nickel	0.39 mg/l
Silver	0.014 mg/l
Zinc	0.41 mg/l
Cyanide	0.06 mg/l
Methylene Chloride	0.21 mg/l
Chloroform	0.40 mg/l
Toluene	0.125 mg/l
1,1,2,2 Tetrachloroethylene	0.14 mg/l
O & P Xylene	0.125 mg/l
Phenol	0.003 mg/l
2,4 Dimethylphenol	0.003 mg/l
1,4 Dichlorobenzene	0.04 mg/l
Isophorone	0.004 mg/l
Naphthalene	0.002 mg/l
Bis (2-Ethylhexyl) Phthalate	
Butyl Benzyl Phthalate	
Di-N-Butyl Phthalate	
Diethyl Phthalate	
Di-N-Octyl Phthalate	0.16 mg/l

(5) State requirements. State requirements and limitations on discharges shall apply in any case where they are more stringent than federal requirements and limitations or those in this chapter.

(6) City's right of revision. The city reserves the right to establish by ordinance more stringent limitations or requirements on discharges to the wastewater disposal system if deemed necessary to comply with the objectives presented in § 18-201 of this chapter.

(7) Excessive discharge. No user shall ever increase the use of process water or, in any way, attempt to dilute a discharge as a partial or complete substitute for adequate treatment to achieve compliance with the limitations contained in the federal categorical pretreatment standards, or in any other pollutant-specific limitation developed by the city or state. (Comment: Dilution may be an acceptable means of complying with some of the prohibitions set forth in § 18-204(1), e.g. the pH prohibition.)

(8) Accidental discharges. Each user shall provide protection from accidental discharge of prohibited materials or other substances regulated by this chapter. Facilities to prevent accidental discharge of prohibited materials shall be provided and maintained at the owner or user's own cost and expense. Detailed plans showing facilities and operating procedures to provide this protection shall be submitted to the city for review, and shall be approved by the city before construction of the facility. All existing users shall complete such a plan by 180 days. No user who commences contribution to the POTW after the effective date of this chapter shall be permitted to introduce pollutants into the system until accidental discharge procedures have been approved by the city. Review and approval of such plans and operating procedures shall not relieve the industrial user from the responsibility to modify the user's facility as necessary to meet the requirements of this chapter. In the case of an accidental discharge, it is the responsibility of the user to immediately telephone and notify the POTW of the incident. The notification shall include location of discharge, type of waste, concentration and volume, and corrective actions.

Written notice: Within five (5) days following an accidental discharge, the user shall submit to the superintendent a detailed written report describing the cause of the discharge and the measures to be taken by the user to prevent similar future occurrences. Such notification shall not relieve the user of any expense, loss, damage, or other liability which may be incurred as a result of damage to the POTW, fish kills, or any other damage to persons or property; nor shall such notification relieve the user of any fines, civil penalties, or other liability which may be imposed by this chapter or other applicable law.

Notice to employees: A notice shall be permanently posted on the user's bulletin board or other prominent place advising employees whom to call in the event of a dangerous discharge. Employers shall insure that all employees who may cause or suffer such a dangerous discharge to occur are advised of the emergency notification procedure. (Ord. #514, May 1988)

18-207. Fees. (1) Purpose. It is the purpose of this section to provide for the recovery costs from users of the city's wastewater disposal system for the implementation of the program established herein. The applicable charges or fees shall be set forth in the city's schedule of charges and fees.

(2) Charges and fees. The city may adopt charges and fees which may include:

- (a) Fees for reimbursement of costs of setting up and operating the city's pretreatment program;
- (b) Fees for monitoring, inspections and surveillance procedures;
- (c) Fees for reviewing accidental discharge procedures and construction;
- (d) Fees for permit applications;
- (e) Fees for filing appeals;
- (f) Fees for consistent removal (by the city) of pollutants otherwise subject to federal pretreatment standards;
- (g) Other fees as the city may deem necessary to carry out the requirements contained herein.

These fees relate solely to the matters covered by this chapter and are separate from all other fees chargeable by the city. (Ord. #514, May 1988)

18-208. Administration. (1) Wastewater contribution permits.

(a) General permits. All significant users proposing to connect to or to contribute to the POTW shall obtain a wastewater discharge permit before connecting to or contributing to the POTW. All existing significant users connected to or contributing to the POTW shall obtain a wastewater contribution permit within 180 days after the effective date of this chapter.

(b) Permit application. Users required to obtain a wastewater contribution permit shall complete and file with the city an application in the form prescribed by the city, and accompanied by a fee of \$300.00. Existing users shall apply for a wastewater contribution permit within 30 days after the effective date of this chapter, and proposed new users shall apply at least 90 days prior to connecting to or contributing to the POTW. In support of the application, the user shall submit, in units and terms appropriate for evaluation, the following information:

- (i) Name, address, and location, (if different from the address);
- (ii) SIC number according to the Standard Industrial Classification Manual, Bureau of the Budget, 1972, as amended;
- (iii) Wastewater constituents and characteristics including but not limited to those mentioned in § 18-204 of this chapter as determined by a reliable analytical laboratory; sampling and analysis shall be performed in accordance with procedure established by the EPA pursuant to Section 304(g) of the Act and contained in 40 CFR, Part 136, as amended;

- (iv) Time and duration of contribution;
- (v) Average daily and 30 minute peak wastewater flow rates, including daily, monthly and seasonal variations if any;
- (vi) Site plans, floor plans, mechanical and plumbing plans and details to show all sewers, sewer connections, and appurtenances by the size, location and elevation;
- (vii) Description of activities, facilities and plant processes on the premises including all materials which are or could be discharged;
- (viii) Where known, the nature and concentration of any pollutants in the discharge which are limited by any city, state, or federal pretreatment standards, and a statement regarding whether or not the pretreatment standards are being met on a consistent bases and if not, whether additional Operation and Maintenance (O&M) and/or additional pretreatment is required for the user to meet applicable pretreatment standards;
- (ix) If additional pretreatment and/or O&M will be required to meet the pretreatment standards; the shortest schedule by which the user will provide such additional pretreatment. The completion date in this schedule shall not be later than the compliance date established for the applicable pretreatment standard:

The following conditions shall apply to this schedule:

(A) The schedule shall contain increments of progress in the form of dates for the commencement and completion of major events leading to the construction and operation of additional pretreatment required for the user to meet the applicable pretreatment standards (e.g., hiring an engineer, completing preliminary plans, completing final plans, executing contract for major components, commencing construction, completing construction, etc.).

(B) No increment referred to in paragraph (A) shall exceed 9 months.

(C) Not later than 14 days following each date in the schedule and the final date for compliance, the user shall submit a progress report to the superintendent including, as a minimum, whether or not it complied with the increment of progress to be met on such date and, if not, the date on which it expects to comply with this increment of progress, the reason for delay, and the steps being taken by the user to return the construction to the schedule

established. In no event shall more than 9 months elapse between such progress reports to the superintendent.

(x) Each product produced by type, amount, process or processes and rate of production;

(xi) Type and amount of raw materials processed (average and maximum per day);

(xii) Number and type of employees, and hours of operation of plant and proposed or actual hours of operation of pretreatment system;

(xiii) Any other information as may be deemed by the city to be necessary to evaluate the permit application.

The city will evaluate the data furnished by the user and may require additional information. After evaluation and acceptance of the data furnished, the city may issue a wastewater contribution permit subject to terms and conditions provided herein.

(c) Permit modifications. Within 9 months of the promulgation of a national categorical pretreatment standard, the wastewater contribution permit of users subject to such standard shall be revised to require compliance with such standard within the time frame prescribed by such standard. Where a user, subject to a national categorical pretreatment standard, has not previously submitted an application for a wastewater contribution permit as required by § 18-208(1)(c), the user shall apply for a wastewater contribution permit within 180 days after the promulgation of the applicable national categorical pretreatment standard. In addition, the user with an existing wastewater contribution permit shall submit to the superintendent within 180 days after the promulgation of an applicable federal pretreatment standard the information required by § 18-208(1)(b)(viii) and (ix).

(d) Permit conditions. Wastewater discharge permits shall be expressly subject to all provisions of this chapter and all other applicable regulations, user charges and fees established by the city. Permits may contain the following:

(i) The unit charge or schedule of user charges and fees for the wastewater to be discharged to a community sewer;

(ii) Limits on the average and maximum wastewater constituents and characteristics;

(iii) Limits on average and maximum rate and time of discharge or requirements for flow regulations and equalization;

(iv) Requirements for installation and maintenance of inspection and sampling facilities;

(v) Specifications for monitoring programs which may include sampling locations, frequency of sampling, number, types and standards for tests and reporting schedule;

(vi) Compliance schedules;

(vii) Requirements for submission of technical reports or discharge reports (see § 18-208(2));

(viii) Requirements for maintaining and retaining plant records relating to wastewater discharge as specified by the city, and affording city access thereto;

(ix) Requirements for notification of the city or any new introduction of wastewater constituents or any substantial change in the volume or character of the wastewater constituents being introduced into the wastewater treatment system;

(x) Requirements for notification of slug discharge as per § 18-209(2);

(xi) Other conditions as deemed appropriate by the city to ensure compliance with this chapter.

(e) Permit duration. Permits shall be issued for a specified time period not to exceed three (3) years. A permit may be issued for a period less than a year or may be stated to expire on a specific date. The user shall apply for permit reissuance a minimum of 180 days prior to the expiration of the user's existing permit. The terms and conditions of the permit may be subject to modification by the city during the term of the permit as limitations or requirements as identified in § 18-204 are modified or other just cause exists. The user shall be informed of any proposed changes in his permit at least 30 days prior to the effective date of change. Any changes or new conditions in the permit shall include a reasonable time schedule for compliance.

(f) Permit transfer. Wastewater discharge permits are issued to a specific user for a specific operation. A wastewater discharge permit shall not be reassigned or transferred or sold to a new owner, new user, different premises, or a new or changed operation without the approval of the city. Any succeeding owner or user shall also comply with the terms and conditions of the existing permit.

(2) Reporting requirements for permittee.

(a) Compliance date report. Within 90 days following the date for final compliance with applicable pretreatment standards or, in the case of a new source, following commencement of the introduction of wastewater into the POTW, any user subject to pretreatment standards and requirements shall submit to the superintendent a report indicating the nature and concentration of all pollutants in the discharge from the regulated processes which are limited by pretreatment standards and

requirements and the average and maximum daily flow for these process units in the user facility which are limited by such pretreatment standards or requirements. The report shall state whether the applicable pretreatment standards or requirements are being met on a consistent basis and, if not, what additional O&M and/or pretreatment is necessary to bring the user into compliance with the applicable pretreatment standards or requirements. This statement shall be signed by an authorized representative of the industrial user, and certified to by a qualified professional.

(b) Periodic compliance reports. (i) Any user subject to a pretreatment standard, after the compliance date of such pretreatment standard, or, in the case of a new source, after commencement of the discharge into the POTW, shall submit to the superintendent during the months of June and December, unless required more frequently in the pretreatment standard or by the superintendent, a report indicating the nature and concentration of pollutants in the effluent which are limited by such pretreatment standards. In addition, this report shall include a record of all daily flows which, during the reporting period, exceeded the average daily flow reported in Paragraph (b)(4) of this section. At the discretion of the superintendent and in consideration of such factors as local high or low flow rates, holidays, budget cycles, etc., the superintendent may agree to alter the months during which the above reports are to be submitted.

(ii) The superintendent may impose mass limitations on users which are using dilution to meet applicable pretreatment standards or requirements, or in other cases where the imposition of mass limitations are appropriate. In such cases, the report required by subparagraph (i) of this paragraph shall indicate the mass of pollutants regulated by pretreatment standards in the effluent of the user. These reports shall contain the results of sampling and analysis of the discharge, including the flow and the nature and concentration, or production and mass where requested by the superintendent, of pollutants contained therein which are limited by the applicable pretreatment standards. The frequency of monitoring shall be prescribed in the applicable pretreatment standard. All analysis shall be performed in accordance with procedure established by the administrator pursuant to Section 304(g) of the Act and contained in 40 CFR, Part 136 and amendments thereto or with any other test procedures approved by the administrator. Sampling shall be performed in accordance with the techniques approved by the administrator.

(Comment:Where 40 CFR, Part 136 does not include a sampling or analytical technique for the pollutant in question, sampling and analysis shall be performed in accordance with the procedures set forth in the EPA publication, Sampling and Analysis Procedures for Screening of Industrial Effluents for Priority Pollutants, April, 1977, and amendments thereto, or with any other sampling and analytical procedures approved by the administrator.)

(3) Monitoring facilities. The city shall require to be provided and operated at the user's own expense, monitoring facilities to allow inspection, sampling, and flow measurement of the building sewer and/or internal drainage systems. The monitoring facility should normally be situated on the user's premises, but the city may, when such a location would be impractical or cause undue hardship on the user, allow the facility to be constructed in the public street or sidewalk area and located so that it will not be obstructed by landscaping or parked vehicles.

There shall be ample room in or near such sampling manhole or facility to allow accurate sampling and preparation of samples for analysis. The facility, sampling, and measuring equipment shall be maintained at all times in a safe and proper operating condition at the expense of the user.

Whether constructed on public or private property, the sampling and monitoring facilities shall be provided in accordance with the city's requirements and all applicable local construction standards and specifications. Construction shall be completed within 90 days following written notification by the city.

(4) Inspection and sampling. The city shall inspect the facilities of any user to ascertain whether the purpose of this chapter is being met and all requirements are being complied with. Persons or occupants of premises where wastewater is created or discharged shall allow the city or their representative ready access at all reasonable times to all parts of the premises for the purposes of inspection, sampling, records and examination or in the performance of any of their duties. The city, approval authority and (where the NPDES state is the approval authority) EPA shall have the right to set up on the user's property such devices as are necessary to conduct sampling inspection, compliance monitoring and/or metering operations. Where a user has security measures in force which would require proper identification and clearance before entry into their premises, the user shall make necessary arrangements with their security guards so that upon presentation of suitable identification, personnel from the city, approval authority and EPA will be permitted to enter, without delay, for the purposes of performing their specific responsibilities.

(5) Pretreatment. Users shall provide necessary wastewater treatment as required to comply with this chapter and shall achieve compliance with all federal categorical pretreatment standards within the time limitations as

specified by the federal pretreatment regulations. Any facilities required to pretreat wastewater to a level acceptable to the city shall be provided, operated, and maintained at the user's expense. Detailed plans showing the pretreatment facilities and operating procedures shall be submitted to the city for review, and shall be acceptable to the city before construction of the facility. The review of such plans and operating procedures will in no way relieve the user from the responsibility of modifying the facility as necessary to produce an effluent acceptable to the city under the provisions of this chapter. Any subsequent changes in the pretreatment facilities or method of operation shall be reported to and be acceptable to the city prior to the user's initiation of the changes.

The city shall annually publish in the LaFollette newspaper a list of the users which were not in compliance with any pretreatment requirement or standards at least once during the 12 previous months. The notification shall also summarize any enforcement actions taken against the user(s) during the same 12 months.

All records relating to compliance with pretreatment standards shall be made available to officials of the EPA or approval authority upon request.

(6) Confidential information. Information and data on a user obtained from reports, questionnaires, permit applications, permits and monitoring programs and from inspections shall be available to the public or other governmental agency without restrictions unless the user specifically requests and is able to demonstrate to the satisfaction of the city that the release of such information would divulge information, processes or methods of production entitled to protection as trade secrets of the user.

When requested by the person furnishing a report, the portions of a report which might disclose trade secrets or secret processes shall not be made available for inspection by the public but shall be made available upon written request to governmental agencies for uses related to this chapter, the National Pollutant Discharge Elimination System (NPDES) Permit, State Disposal System permit and/or the pretreatment programs; provided, however, that such portions of a report shall be available for use by the state or any state agency in judicial review or enforcement proceedings involving the person furnishing the report. Wastewater constituents and characteristics will not be recognized as confidential information. (Ord. #514, May 1988)

18-209. Enforcement. (1) Harmful contributions. The city may suspend the wastewater treatment service and/or a wastewater contribution permit when such suspension is necessary in the opinion of the city, in order to stop an actual or threatened discharge which presents or may present an imminent or substantial endangerment to the health or welfare of persons, to the environment, causes interference to the POTW or causes the city to violate any condition of its NPDES permit.

Any person notified of a suspension of the wastewater treatment service and/or the wastewater contribution permit shall immediately stop or eliminate the contribution. In the event of a failure of the person to comply voluntarily with the suspension order, the city shall take such steps as deemed necessary including immediate severance of the sewer connection, to prevent or minimize damage to the POTW system or endangerment to any individuals. The city shall reinstate the wastewater contribution permit and/or the wastewater treatment service upon proof of the elimination of the non-complying discharge. A detailed written statement submitted by the user describing the cases of the harmful contribution and the measure taken to prevent any future occurrence shall be submitted to the city within 15 days of the date of occurrence.

(2) Revocation of permit. Any user who violates the following conditions of this chapter, or applicable state and federal regulations is subject to having his permit revoked in accordance with the procedures of § 18-207:

- (a) Failure of user to factually report the wastewater constituents and characteristics of his discharge;
- (b) Failure of the user to report significant changes in operations, or wastewater constituents and characteristics;
- (c) Refusal of reasonable access to their user's premises for the purpose of inspecting or monitoring; or
- (d) Violation of conditions of the permit.

(3) Notification of violation. Whenever the city finds that any user has violated or is violating this chapter, wastewater contribution permit, or any prohibition, limitation or requirements contained herein, the city may serve upon such person a written notice stating the nature of the violation. Within 30 days of the date of the notice, a plan for the satisfactory correction thereof shall be submitted to the city by the user.

(4) Show cause hearing. (a) The city may order any user who causes or allows an unauthorized discharge to enter the POTW to show cause before the city council of the City of LaFollette why the proposed enforcement action should not be taken. A notice shall be served on the user specifying the time and place of a hearing to be held by the city council of the City of LaFollette regarding the violation, the reasons why the action is to be taken, the proposed enforcement action, and directing the user to show cause before the city council of the City of LaFollette why the proposed enforcement action should not be taken. The notice of the hearing shall be served personally or by registered or certified mail (return receipt requested) at least ten (10) days before the hearing. Service may be made on any agent or office of a corporation.

(b) The city council of the City of LaFollette may itself conduct the hearing and take the evidence, or may designate any of its members or any officer to employee of the water and sewer department to:

(i) Issue in the name of the city council of the City of LaFollette notices of hearings requesting the attendance and testimony of witnesses and the production of evidence relevant to any matter involved in such hearings;

(ii) Take the evidence;

(iii) Transmit a report of the evidence and hearing, including transcripts and other evidence, together with recommendations to the city council of the City of LaFollette for action thereon.

(c) At any hearing held pursuant to this chapter, testimony taken must be under oath and recorded stenographically. The transcript, so recorded, will be made available to any member of the public or any party to the hearing upon payment of the usual charges thereof.

(d) After the city council of the City of LaFollette has reviewed the evidence, it may issue an order to the user responsible for the discharge directing that, following a specified time period, the sewer service be discontinued unless adequate treatment facilities, devices or other related appurtenances shall have been installed on existing treatment facilities, devices or other related appurtenances are properly operated. Further orders and directives as are necessary and appropriate may be issued.

(5) Legal action. If any person discharges sewage, industrial wastes or other wastes into the city's wastewater disposal system contrary to the provisions of this chapter, federal or state pretreatment requirements, or any order of the city, the city attorney may commence an action for appropriate legal and/or equitable relief in the Circuit or Chancery Court of this county. (Ord. #514, May 1988)

18-210. Penalty: costs. (1) Civil penalties. Any user who is found to have violated an order of the city council of the City of LaFollette, or who willfully or negligently failed to comply with any provision of this chapter and the orders, rules, regulations and permits issued hereunder, shall be fined not more than fifty dollars for each offense. Each day on which a violation shall occur or continue shall be deemed a separate and distinct offense. In addition to the penalties provided herein, the city may recover reasonable attorney's fees, court costs, court reporters' fees, and other expenses of litigation by appropriate suit at law against the persons found to have violated this chapter or the orders, rules, regulations, and permits issued hereunder.

(2) Falsifying information. Any person who knowingly makes any false statements, representation or certification in any application, record, report, plan or other document filed or required to be maintained pursuant to this chapter, or wastewater contribution permit, or who falsifies, tampers with,

or knowingly renders inaccurate any monitoring device or method required under this chapter, shall, upon conviction, be punished by a fine of not more than \$50.00. (Ord. #514, May 1988)

18-211. Protection from damage. No unauthorized person shall maliciously, willfully, or negligently break, damage, destroy, uncover, deface or tamper with any structure, appurtenance, or equipment which is a part of the municipal sewage works. Any person violating this provision shall be subject to immediate arrest under charge of disorderly conduct. (Ord. #514, May 1988)

18-212. Powers and authority of inspectors. The superintendent and other duly authorized employees of the city bearing proper credentials and identification shall be permitted to enter upon all properties for the purposes of inspection, observation, measurement, sampling, and testing, in accordance with the provisions of this chapter. (Ord. #514, May 1988)

CHAPTER 3**CROSS CONNECTIONS, AUXILIARY INTAKES, ETC.¹****SECTION**

- 18-301. Definitions.
- 18-302. Compliance.
- 18-303. Regulated.
- 18-304. Statement required.
- 18-305. Inspections.
- 18-306. Right of entry.
- 18-307. Violations.
- 18-308. Contamination containment.
- 18-309. Protection.
- 18-310. Penalties.

18-301. Definitions. The following definitions and terms shall apply in the interpretation and enforcement of this chapter:

(1) "Public water supply." The waterworks system furnishing water to the City of LaFollette, Tennessee for general use and which supply is recognized as the public water supply by the Tennessee Department of Health.

(2) "Cross connection." Any physical connection whereby the public water supply is connected with any other water supply system, whether public or private, either inside or outside of any building or buildings, in such manner that a flow of water into the public water supply is possible either through the manipulation of valves or because of any other arrangement.

(3) "Auxiliary intake." Any piping connection or other device whereby water may be secured from a source other than that normally used.

(4) "Bypass." Any system of piping or other arrangement whereby the water may be diverted around any part or portion of a water purification plant.

(5) "Interconnection." Any system of piping or other arrangement whereby the public water supply is connected directly with a sewer, drain, conduit, pool, storage reservoir, or other device which does or may contain sewage or other waste or liquid which would be capable of imparting contamination to the public water supply.

¹Municipal code references

Plumbing code: title 12.

Water and sewer system administration: title 18.

Wastewater treatment: title 18.

(6) "Person." Any and all persons, natural or artificial, including any individual, firm, or association, and any municipal or private corporation organized or existing under the laws of this or any other state or country. (1975 Code, § 8-301)

18-302. Compliance. The City of LaFollette, Tennessee Public Water Supply is to comply with Tennessee Code Annotated, §§ 68-221-701 through 68-221-720 as well as the Rules and Regulations for Public Water Supplies, legally adopted in accordance with this code, which pertain to cross connections, auxiliary intakes, bypasses, and interconnections, and establish an effective ongoing program to control these undesirable water uses. (1975 Code, § 8-302)

18-303. Regulated. It shall be unlawful for any person to cause a cross connection to be made, or allow one to exist for any purpose whatsoever, unless the construction and operation of same have been approved by the Tennessee Department of Health and the operation of such cross connection, auxiliary intake, bypass or interconnection is at all times under the direct supervision of the Superintendent of the LaFollette Water Department of the City of LaFollette, Tennessee. (1975 Code, § 8-303)

18-304. Statement required. Any person whose premises are supplied with water from the public water supply and who also has on the same premises a separate source of water supply, or stores water in an uncovered or unsanitary storage reservoir from which the water stored therein is circulated through a piping system, shall file with the Superintendent of the City of LaFollette Waterworks a statement of the non-existence of unapproved or unauthorized cross connections, auxiliary intakes, bypasses, or interconnections. Such statement shall also contain an agreement that no cross connection, auxiliary intake, bypass, or interconnection will be permitted upon the premises. (1975 Code, § 8-304)

18-305. Inspections. It shall be the duty of the LaFollette Public Water Supply to cause inspections to be made of all properties served by the public water supply where cross connections with the public water supply are deemed possible. The frequency of inspections and reinspection, based on potential health hazards involved, shall be established by the Superintendent of the LaFollette Public Water Supply and as approved by the Tennessee Department of Health. (1975 Code, § 8-305)

18-306. Right of entry. The superintendent or his authorized representative shall have the right to enter, at any reasonable time, any property served by a connection to the LaFollette Public Water Supply for the

purpose of inspecting the piping system or systems therein for cross connections, auxiliary intakes, bypasses, or interconnections. On request, the owner, lessee, or occupant of any property so served shall furnish to the inspection agency any pertinent information regarding the piping system or systems on such property. The refusal of such information or refusal of access, when requested, shall be deemed evidence of the presence of cross connections. (1975 Code, § 8-306)

18-307. Violations. Any person who now has cross connections, auxiliary intakes, bypasses, or interconnections in violation of the provisions of this chapter shall be allowed a reasonable time within which to comply with the provisions of this chapter. After a thorough investigation of existing conditions and an appraisal of the time required to complete the work, the amount of time shall be designated by the Superintendent of the LaFollette Public Water Supply.

The failure to correct conditions threatening the safety of the public water system as prohibited by this chapter and the Tennessee Code Annotated, § 68-221-711, within a reasonable time and within the time limits set by the LaFollette Public Water Supply, shall be grounds for denial of water service. If proper protection has not been provided after a reasonable time, the utility shall give the customer legal notification that water service is to be discontinued and shall physically separate the public water supply from the customer's on-site piping system in such a manner that the two systems cannot again be connected by an unauthorized person.

Where cross connections, interconnections, auxiliary intakes, or bypasses are found that constitute an extreme hazard of immediate concern of contaminating the public water system, the manager of the utility shall require that immediate corrective action be taken to eliminate the threat to the public water system. Immediate steps shall be taken to disconnect the public water supply from the on-site piping system unless the imminent hazard(s) is corrected immediately. (1975 Code, § 8-307)

18-308. Contamination containment. Where the nature of use of the water supplied a premises by the water department is such that it is deemed:

- (1) Impractical to provide an effective air-gap separation.
- (2) That the owner and/or occupant of the premises cannot, or is not willing, to demonstrate to the official in charge of the system, or his designated representative, that the water use and protective features of the plumbing are such as to propose no threat to the safety or potability of the water supply.
- (3) That the nature and mode of operation within a premises are such that frequent alterations are made to the plumbing.
- (4) There is a likelihood that protective measures may be subverted, altered, or disconnected.

The Superintendent of the LaFollette Public Water Supply, or his designated representative, shall require the use of an approved protective device on the service line serving the premises to assure that any contamination that may originate in the customer's premises is contained therein. The protective device shall be a reduced pressure zone type backflow preventer approved by the Tennessee Department of Health as to manufacture, model, and size. The method of installation of backflow protective devices shall be approved by the Superintendent of the Public Water Supply prior to installation and shall comply with the criteria set forth by the Tennessee Department of Health. The installation shall be at the expense of the owner or occupant of the premises.

Personnel of the LaFollette Public Water Supply shall have the right to inspect and test the device or devices on an annual basis or whenever deemed necessary by the superintendent or his designated representative. Water service shall not be disrupted to test the device without the knowledge of the occupant of the premises.

Where the use of water is critical to the continuance of normal operations or protection of life, property, or equipment, duplicate units shall be provided to avoid the necessity of discontinuing water service to test or repair the protective device or devices. Where it is found that only one unit has been installed and the continuance of service is critical, the superintendent shall notify, in writing, the occupant of the premises of plans to discontinue water service and arrange for a mutually acceptable time to test and/or repair the device. The water supply shall require the occupant of the premises to make all repairs indicated promptly, to keep the unit(s) working properly, and the expense of such repairs shall be borne by the owner or occupant of the premises. Repairs shall be made by qualified personnel acceptable to the Superintendent of the LaFollette Public Water Supply.

If necessary, water service shall be discontinued (following legal notification) for failure to maintain backflow prevention devices in proper working order. Likewise, the removal, bypassing, or altering of the protective device(s) or the installation thereof so as to render the device(s) ineffective shall constitute grounds for discontinuance of water service. Water service to such premises shall not be restored until the customer has corrected or eliminated such conditions or defects to the satisfaction of the LaFollette Public Water Supply. (1975 Code, § 8-308)

18-309. Protection. The potable water supply made available to premises served by the public water supply shall be protected from possible contamination as specified herein. Any water outlet which could be used for potable or domestic purposes and which is not supplied by the potable system must be labeled in a conspicuous manner as:

WATER UNSAFE

FOR DRINKING

Minimum acceptable sign shall have black letters at least one-inch high located on a red background. (1975 Code, § 8-309)

18-310. Penalties. Any person who neglects or refuses to comply with any of the provisions of this chapter shall be deemed guilty of a misdemeanor and, upon conviction therefor, shall be fined accordingly. (1975 Code, § 8-310)