TITLE 11

PLANNING AND ZONING

CHAPTER

- 1. MUNICIPAL PLANNING COMMISSION.
- 2. ZONING ORDINANCE.
- 3. AIRPORT ZONING ORDINANCE.
- 4. FLOODPLAIN ZONING ORDINANCE.

CHAPTER 1

MUNICIPAL PLANNING COMMISSION¹

SECTION

- 11-101. Creation and membership.
- 11-102. Organization, powers, duties, etc.
- 11-103. Additional powers.

11-101. Creation and membership. Pursuant to the provisions of section 13-4-101 of the Tennessee Code Annotated there is hereby created a municipal planning commission, hereinafter referred to as the planning commission. The planning commission shall consist of nine (9) members; two of these shall be the mayor and a councilman selected by the city council; the other seven (7) members shall be appointed by the mayor. All members of the planning commission shall serve as such without compensation. Except for the initial appointments, the terms of the seven (7) members appointed by the mayor shall be for three (3) years each. Of the seven (7) members to be first appointed by the mayor, as authorized by this section, one (1) member shall be appointed for one (1) year, three (3) members shall be appointed for two (2) years, and the other three (3) members shall be appointed for three (3) years so that the term of at least one (1) member expires each year. The term of office for each of the seven (7) members to be appointed initially shall begin as of October 1, 1973. The term of all future appointments under this ordinance shall begin as of October 1st in succeeding years.

The terms of the mayor and the councilman shall run concurrently with the mayor's term of office. Any vacancy in an appointive membership shall be filled for the unexpired term by the mayor. (1979 code, § 11-101)

11-102. <u>Organization</u>, powers, duties, etc. The planning commission shall be organized and shall carry out its powers, functions and duties in accordance with title 13 of the <u>Tennessee Code Annotated</u>. (1979 code, § 11-102)

¹Article VII, section 7.070 of the Zoning Ordinance for the City of Shelbyville, Tennessee was replaced by Ordinance #2013-925, July 2013, "Board of Zoning Appeals" and is available for review in the city recorder's office.

11-103. <u>Additional powers</u>. Having been designated as a regional planning commission, the municipal planning commission shall have the additional powers granted by, and shall otherwise be governed by the provisions of the state law relating to regional planning commissions. (1979 code, § 11-103)

CHAPTER 2

ZONING ORDINANCE

SECTION

11-201. Land use to be governed by zoning ordinance.

11-201. <u>Land use to be governed by zoning ordinance</u>. Land use within the City of Shelbyville shall be governed by Ordinance Number 2014-937, titled "Zoning Ordinance of Shelbyville, Tennessee," and any amendments thereto.¹

¹Ordinance No. 2014-937, March 2014, and any amendments thereto, are published as separate documents and are of record in the office of the city recorder.

CHAPTER 3

AIRPORT ZONING ORDINANCE¹

SECTION

- 11-301. Short title.
- 11-302. Definitions.
- 11-303. Airport zoning map.
- 11-304. Zones.
- 11-305. Height limits.
- 11-306. Use restrictions.
- 11-307. Variances.
- 11-308. Permits.
- 11-309. Hazard marking and lighting.
- 11-310. General provisions.
- 11-311. Appeals.
- 11-312. Administrative agency.
- 11-313. Board of zoning appeals.
- 11-314. Amendments.
- 11-315. Penalties.
- 11-301. <u>Short title</u>. This chapter shall be known and may be cited as the "Airport Zoning Ordinance of the Shelbyville Municipal Airport." (1979 code, § 11-1101)
- 11-302. <u>Definitions</u>. As used in this chapter, unless the context otherwise requires:
 - (1) "Airport" means "Bomar Field," the Shelbyville Municipal Airport.
- (2) "Airport hazard" means any structure or tree or use of land which obstructs the airspace required for the flight of aircraft in landing or taking-off at the airport or is otherwise hazardous to such landing or taking-off of aircraft.
- (3) "Non-conforming use" means any structure, tree, or use of land which does not conform to a regulation prescribed in this chapter or an amendment thereto, as of the effective date of such regulation.

¹It is the intention of the city council in adopting this chapter merely to continue in effect the provisions of ordinance No. 105 as amended to date. It expressly is not the intention of the city council to hereby enact any new airport zoning regulations.

For provisions relating to the Shelbyville Airport Authority see title 1, chapter 9.

- (4) "Person" means any individual, firm, co-partnership, corporation, company, association, joint stock association or body politic, and includes any trustee, receiver, assignee, or other similar representative thereof.
- (5) "Structure" means any object constructed or installed by man, including, but without limitation, buildings, towers, smokestacks, and overhead transmission lines.
- (6) "Landing area" means the area of the airport used for the landing, take-off, or taxiing of aircraft.
 - (7) "Tree" means any object of natural growth. (1979 code, § 11-1102)
- 11-303. <u>Airport zoning map</u>. In order to outline definitely the horizontal and vertical limits beyond which the projection of any structure or tree will constitute an airport hazard, the Airport Zoning Map, dated January 26, 1965, of Lag Field, Shelbyville Municipal Airport, Shelbyville, Tennessee, of record in the office of the city recorder, is hereby incorporated into this chapter and made a part hereof.
- (1) The established elevation of the airport is 802 feet above mean sea level
- (2) The airport reference point is established at a location described as follows: The exact center of the main runway. (1979 code, § 11-1103)
- 11-304. Zones. In order to carry out the purposes of this chapter, airport approach surface zones, horizontal surface zones, conical surface zones, and transitional surface zones are hereby established as hereinafter defined and as shown on the airport zoning map.
- (1) <u>Approach surface zone</u>. The approach surface zone is an inclined plane located directly above the approach area. The dimensions of the approach area are measured horizontally. The approach areas for each particular runway are symmetrically located with respect to the extended runway center lines and have lengths and widths as shown on the airport zoning map, which also shows the slopes of the respective approach surface zones.
- (2) <u>Horizontal surface zone</u>. The horizontal surface zone is a plane, circular in shape, with its height 150 feet above the established airport elevation and having a radius from the airport reference point as indicated on the airport zoning map.
- (3) <u>Conical surface zone</u>. The conical surface zone extends upward and outward from the periphery and outward from the horizontal surface zone with a slope of 20:1 measured in a vertical plane passing through the airport reference point. Measuring radially outward from the periphery of the horizontal surface zone, the conical surface extends for a horizontal distance as shown on the airport zoning map.
- (4) <u>Transitional surface zones</u>. The transitional surface zones are inclined planes with a slope of 7:1 ,measured upward and outward in a vertical plane at a right angle to the center line of the runway. The transitional surface

zones, symmetrically located on either side of the runway, extend upward and outward from a line on either side of the runway which is parallel to and level with the runway center line. These parallel lines are at a horizontal distance from the runway center line equal to one-half of the minimum width of each approach area as shown on the airport zoning map. (1979 code, § 11-1104)

11-305. Height limits. Except as otherwise provided in this chapter, no structure, or tree shall be erected, altered, allowed to grow, or maintained so as to penetrate the plane which composes the airport approach surface zone, horizontal surface zone conical surface zone or transitional surface zone, by being of a height in excess of the height limits herein established for such zone. For purposes of this regulation, height limits shown on the airport zoning map are hereby established for each of the zones in question. Notwithstanding any other provisions of this chapter to the contrary, the height limits prescribed by this chapter shall not establish for any particular parcel of land at any particular point within such parcel, a height limit of less than sixty (60) feet above the surface elevation of the land at that point. (1979 code, § 11-1105)

11-306. Use restrictions. Notwithstanding any other provisions of this chapter, no use may be made of land within any airport approach surface zone, horizontal surface zone, conical surface zone, or transitional surface zone, in such manner as to create electrical interference with radio communication between the airport and aircraft, make it difficult for flyers to distinguish between airport lights and others, result in glare in the eyes of flyers using the airport, impair visibility in the vicinity of the airport, or otherwise endanger the landing, taking-off, or maneuvering of aircraft. Except as otherwise provided in this chapter, it shall be unlawful to put on land located within an airport approach surface zone, horizontal surface zone, conical surface zone, or transitional surface zones the following: Churches and other places of worship; clubhouses and other meeting planes; community center buildings; gymnasiums or stadiums; libraries; schools; colleges; hospitals; sanitariums or other public, semi-public, or private educational, health, or welfare institutions or facilities: and any governmental office or building, the facilities of which involves the concentration of people. (1979 code, § 11-1106)

11-307. <u>Variances</u>. Any person desiring to erect any structure or increase the height of any structure, or permit the growth of any tree, or use his property, not in accordance with the regulations prescribed in this chapter, may apply for a variance therefrom. Such variance shall be allowed where a literal application of enforcement of the regulations would result in practical difficulty or unnecessary hardship and the relief granted would not be contrary to the public interest but substantial justice and be in accordance with the spirit of this chapter. (1979 code, § 11-1107)

- 11-308. <u>Permits</u>. (1) <u>Future uses</u>. No material change shall be made in the use of land, and no structure or tree shall be erected, altered, planted, or otherwise established in any airport approach surface zone, horizontal surface zone, conical surface zone, or transitional surface zone, unless a permit therefor shall have been applied for and granted. Each such application shall indicate the purpose for which the permit is desired with sufficient particularity to permit it to be determined whether the resulting use, structure, or tree would conform to the regulations herein prescribed. If such determination is in the affirmative, the permit applied for shall be granted.
- (2) Existing uses. Before any existing use, structure, or tree may replaced, substantially altered, or repaired, rebuilt, allowed to grow higher, or replanted within any airport approach surface zone, horizontal surface zone, conical surface zone, or transitional surface zone which would violate any of the within set forth provisions a permit must be secured authorizing such replacement, change, or repair. No such permit shall be granted that would allow the establishment or creation of an airport hazard or permit a non-conforming use, structure, or tree to be made or become higher, or become a greater hazard to air navigation than it was on the effective date of these provisions or than it is when the application for a permit is made. Except as indicated, all applications for a permit for the replacement, change, or repair of any existing use, structure, or tree shall be granted. (1979 code, § 11-1108)
- 11-309. <u>Hazard marking and lighting</u>. Any permit or variance granted under section 11-307 or 11-308 may, if such action is deemed advisable to effectuate the purposes of this chapter and reasonable in the circumstances, be so conditioned as to require the owner of the structure or tree in question to permit the Shelbyville Airport Commission, at its own expense, to install, operate, and maintain thereon such markers and lights as may be necessary to indicate to flyers the presence of an airport hazard. (1979 code, § 11-1109)
- 11-310. General provisions. Nothing in this chapter is intended to prohibit the normal and ordinary domestic and/or farm use of electrical tools, appliances, or lighting in the various zones hereinbefore designated. It is further provided that existing uses, structures, or trees in existence on the date of the passage of these provisions and constituting violations of same at that time, are excepted provisions hereof; but this exception does not apply to existing trees which may hereinafter become a violation. (1979 code, § 11-1110)
- 11-311. <u>Appeals</u>. (1) Any person aggrieved, or any taxpayer affected, by any decision of the City of Shelbyville made in the administration of this chapter, or the Shelbyville Airport Commission, if of the opinion that a decision of the chief enforcement officer is an improper application of this chapter may appeal to the board of zoning appeals for which provision is made in section 11-313.

- (2) All appeals taken under this section must be taken within a reasonable time, as provided by the rules of the board, by filing with the board of zoning appeals a notice of appeal specifying the grounds thereof. The chief enforcement officer shall forthwith transmit to the board all the papers constituting the record upon which the action appealed from was taken.
- (3) An appeal shall stay all proceedings in furtherance of the action appealed from, unless the chief enforcement officer certifies to the board, after the notice of appeal has been filed with it, that by reason of the facts stated in the certificate a stay would, in his opinion, cause imminent peril to life or property. In such case, proceedings shall not be stayed otherwise than by order of the board on notice to the chief enforcement officer and on due cause shown.
- (4) The board shall fix a reasonable time for the hearing of the appeal, give public notice, and due notice to the parties in interest, and decide the same within a reasonable time. Upon the hearing any party may appear in person or by agent or by attorney.
- (5) The board may, in conformity with the provisions of this chapter, reverse or affirm wholly or partly, or modify the order, requirement, decision, or determination appealed from and may make such order, requirement, decision, or determination as ought to be made.
- (6) The board shall make written findings of fact and conclusions of law giving the facts upon which it acted and its legal conclusions from such facts in reversing, or affirming, or modifying any order, requirement, decision, or determination which comes before it under the provisions of this chapter.
- (7) The concurring vote of a majority of the members of the board shall be sufficient to reverse any order, requirement, decision, or determination of the chief enforcement officer, or to decide in favor of the applicant on any matters upon which it is required to pass under this chapter, or to affect any variation in this chapter. (1979 code, § 11-1111)
- 11-312. Administrative agency. The city building inspector is hereby designated the administrative agency charged with the duty of administering and enforcing the regulations herein prescribed. The duties of the city building inspector shall include that of hearing and deciding all applications for permits under section 11-308, but the city building inspector shall not have or exercise any of the powers or duties herein delegated to the board of zoning appeals. (1979 code, § 11-1112)
- 11-313. <u>Board of zoning appeals</u>. (1) The board of zoning appeals, heretofore created, have and exercise the following powers:

¹See the city's zoning ordinance of record in the recorder's office.

- (a) To hear and decide appeals from any order, requirement, decision or determination made by the city building inspector in the enforcement of this chapter;
- (b) To hear and decide special exceptions to the terms of this chapter upon which such board may be required to pass by subsequent ordinances:
 - (c) To hear and decide specific variances under section 11-308.
- (2) The board shall adopt additional rules for its governance and procedure in harmony with the provisions of this chapter. Meetings of the board shall be held at the call of the chairman and at such other times as the board may determine. The chairman, or in his absence the acting chairman, may administer oaths and compel the attendance of witnesses. All hearings of the board shall be public. The board shall keep minutes of its proceedings, showing the vote of each member upon each question, or if absent or failing to vote, indicating such fact, and shall keep records of its examinations and other official actions, all of which shall immediately be filed in the office of the board and shall be a public record. (1979 code, § 11-1113)
- 11-314. Amendments. The city council of the City of Shelbyville may from time to time amend the boundary, shape, or regulations of any zone or any other provision of this chapter. No such amendment shall become effective unless the same is first submitted for the review of the Shelbyville Municipal Airport Commission and for approval, disapproval, or suggestions to the City of Shelbyville Planning Commission. If said planning commission within thirty (30) days disapproves any such submission, it shall require the favorable vote of a majority of the entire membership of the city council to become effective. If the planning commission neither approves or disapproves such proposed amendment within thirty (30) days after such submission, the action on such amendment by the commission shall be deemed favorable. introduction of an amendment, the city recorder shall be instructed to publish a notice for such a request for an amendment together with a notice of the time set for public hearing by the city council on the requested change. The notice shall be published one (1) time in a newspaper of general circulation. Action on the proposed amendment by the city council shall take place no sooner than fifteen (15) days after the date of publication of such notice. (1979 code, § 11-1114)
- 11-315. <u>Penalties</u>. Each violation of this chapter or of any ordinance, or regulation, order, or ruling promulgated hereunder shall be punishable by a fine under the general penalty clause for this code. (1979 code, § 11-1115)

CHAPTER 4

FLOODPLAIN ZONING ORDINANCE

SECTION

- 11-401. Statutory authorization, findings of fact, purpose and objectives.
- 11-402. Definitions.
- 11-403. General provisions.
- 11-404. Administration.
- 11-405. Provisions for flood hazard reduction.
- 11-406. Variance procedures.
- 11-407. Legal status provisions.

11-401. Statutory authorization, findings of fact, purpose and objectives.

- (1) <u>Statutory authorization</u>. The Legislature of the State of Tennessee has in <u>Tennessee Code Annotated</u>, §§ 13-7-201 through 13-7-210, delegated the responsibility to local governmental units to adopt regulations designed to promote the public health, safety, and general welfare of its citizenry. Therefore, the City of Shelbyville, Tennessee, Mayor and City Council do ordain as follows:
 - (2) <u>Findings of fact</u>. (a) The City of Shelbyville, Tennessee, Mayor and its legislative body wishes to establish eligibility in the National Flood Insurance Program (NFIP) and in order to do so must meet the NFIP regulations found in Title 44 of the Code of Federal Regulations (CFR), ch. l, section 60.3.
 - (b) Areas of the City of Shelbyville, Tennessee are subject to periodic inundation which could result in loss of life and property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood protection and relief, and impairment of the tax base, all of which adversely affect the public health, safety and general welfare.
 - (c) Flood losses are caused by the cumulative effect of obstructions in floodplains, causing increases in flood heights and velocities; by uses in flood hazard areas which are vulnerable to floods; or construction which is inadequately elevated, flood proofed, or otherwise unprotected from flood damages.
- (3) <u>Statement of purpose</u>. It is the purpose of this ordinance to promote the public health, safety and general welfare and to minimize public and private losses due to flood conditions in specific areas. This ordinance is designed to:
 - (a) Restrict or prohibit uses which are vulnerable to flooding or erosion hazards, or which result in damaging increases in erosion, flood heights, or velocities;
 - (b) Require that uses vulnerable to floods, including community facilities, be protected against flood damage at the time of initial construction;

- (c) Control the alteration of natural floodplains, stream channels, and natural protective barriers which are involved in the accommodation of floodwaters;
- (d) Control filling, grading, dredging and other development which may increase flood damage or erosion;
- (e) Prevent or regulate the construction of flood barriers which will unnaturally divert flood waters or which may increase flood hazards to other lands.
- (4) <u>Objectives</u>. The objectives of this ordinance are:
 - (a) To protect human life, health, safety and property;
- (b) To minimize expenditure of public funds for costly flood control projects;
- (c) To minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the general public:
 - (d) To minimize prolonged business interruptions;
- (e) To minimize damage to public facilities and utilities such as water and gas mains, electric, telephone and sewer lines, streets and bridges located in flood prone areas;
- (f) To help maintain a stable tax base by providing for the sound use and development of flood prone areas to minimize blight in flood areas;
- (g) To ensure that potential homebuyers are notified that property is in a flood prone area;
- (h) To establish eligibility for participation in the NFIP. (as replaced by Ord. #2014-932, Jan. 2014)
- 11-402. <u>Definitions</u>. Unless specifically defined below, words or phrases used in this ordinance shall be interpreted as to give them the meaning they have in common usage and to give this ordinance its most reasonable application given its stated purpose and objectives.
- (1) "Accessory structure" means a subordinate structure to the principal structure on the same lot and, for the purpose of this ordinance, shall conform to the following:
 - (a) Accessory structures shall only be used for parking of vehicles and storage.
 - (b) Accessory structures shall be designed to have low flood damage potential.
 - (c) Accessory structures shall be constructed and placed on the building site so as to offer the minimum resistance to the flow of floodwaters.
 - (d) Accessory structures shall be firmly anchored to prevent flotation, collapse, and lateral movement, which otherwise may result in damage to other structures.

- (e) Utilities and service facilities such as electrical and heating equipment shall be elevated or otherwise protected from intrusion of floodwaters.
- (2) "Addition (to an existing building)" means any walled and roofed expansion to the perimeter or height of a building.
- (3) "Appeal" means a request for a review of the local enforcement officer's interpretation of any provision of this ordinance or a request for a variance.
- (4) "Area of shallow flooding" means a designated AO or AH Zone on a community's Flood Insurance Rate Map (FIRM) with one percent (1%) or greater annual chance of flooding to an average depth of one to three feet (1' -- 3') where a clearly defined channel does not exist, where the path of flooding is unpredictable and indeterminate; and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow.
- (5) "Area of special flood-related erosion hazard" is the land within a community which is most likely to be subject to severe flood-related erosion losses. The area may be designated as Zone E on the Flood Hazard Boundary Map (FHBM). After the detailed evaluation of the special flood-related erosion hazard area in preparation for publication of the FIRM, Zone E may be further refined.
 - (6) "Area of special flood hazard" see "Special flood hazard area."
- (7) "Base flood" means the flood having a one percent (1%) chance of being equaled or exceeded in any given year. This term is also referred to as the 100-year floor or the one percent (1%) annual chance flood.
- (8) "Basement" means any portion of a building having its floor subgrade (below ground level) on all sides.
 - (9) "Building" see "structure."
- (10) "Development" means any man-made change to improved or unimproved real estate, including, but not limited to, buildings or other structures, mining, dredging, filling, grading, paving, excavating, drilling operations, or storage of equipment or materials.
- (11) "Elevated building" means a non-basement building built to have the lowest floor of the lowest enclosed area elevated above the ground level by means of solid foundation perimeter walls with openings sufficient to facilitate the unimpeded movement of floodwater, pilings, columns, piers, or shear walls adequately anchored so as not to impair the structural integrity of the building during a base flood event.
- (12) "Emergency flood insurance program" or "emergency program" means the program as implemented on an emergency basis in accordance with section 1336 of the Act. It is intended as a program to provide a first layer amount of insurance on all insurable structures before the effective date of the initial FIRM.
- (13) "Erosion" means the process of the gradual wearing away of land masses. This peril is not "per se" covered under the program.

- (14) "Exception" means a waiver from the provisions of this ordinance which relieves the applicant from the requirements of a rule, regulation, order or other determination made or issued pursuant to this ordinance.
- (15) "Existing construction" means any structure for which the "start of construction" commenced before the effective date of the initial floodplain management code or ordinance adopted by the community as a basis for that community's participation in the NFIP.
- (16) "Existing manufactured home park or subdivision" means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including, at a minimum, the installation of utilities, the construction of streets, final site grading or the pouring of concrete pads) is completed before the effective date of the first floodplain management code or ordinance adopted by the community as a basis for that community's participation in the NFIP.
 - (17) "Existing structures" see "existing construction."
- (18) "Expansion to an existing manufactured home park or subdivision" means the preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads).
- (19) "Flood" or "flooding" means a general and temporary condition of partial or complete inundation of normally dry land areas from:
 - (a) The overflow of inland or tidal waters.
 - (b) The unusual and rapid accumulation or runoff of surface waters from any source.
- (20) "Flood elevation determination" means a determination by the Federal Emergency Management Agency (FEMA) of the water surface elevations of the base flood, that is, the flood level that has a one percent (1%) or greater chance of occurrence in any given year.
- (21) "Flood elevation study" means an examination, evaluation and determination of flood hazards and, if appropriate, corresponding water surface elevations, or an examination, evaluation and determination of mudslide (i.e., mudflow) or flood-related erosion hazards.
- (22) "Flood Hazard Boundary Map (FHBM)" means an official map of a community, issued by FEMA, where the boundaries of areas of special flood hazard have been designated as Zone A.
- (23) "Flood Insurance Rate Map (FIRM)" means an official map of a community, issued by FEMA, delineating the areas of special flood hazard or the risk premium zones applicable to the community.
- (24) "Flood insurance study" is the official report provided by FEMA, evaluating flood hazards and containing flood profiles and water surface elevation of the base flood.
- (24) "Floodplain" or "floodprone area" means any land area susceptible to being inundated by water from any source (see definition of "flooding").

- (25) "Floodplain management" means the operation of an overall program of corrective and preventive measures for reducing flood damage, including but not limited to emergency preparedness plans, flood control works and floodplain management regulations.
- (26) "Flood protection system" means those physical structural works for which funds have been authorized, appropriated, and expended and which have been constructed specifically to modify flooding in order to reduce the extent of the area within a community subject to a "special flood hazard" and the extent of the depths of associated flooding. Such a system typically includes hurricane tidal barriers, dams, reservoirs, levees or dikes. These specialized flood modifying works are those constructed in conformance with sound engineering standards.
- (27) "Floodproofing" means any combination of structural and nonstructural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities and structures and their contents.
- (28) "Flood-related erosion" means the collapse or subsidence of land along the shore of a lake or other body of water as a result of undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high water level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature, such as a flash flood, or by some similarly unusual and unforeseeable event which results in flooding.
- (29) "Flood-related erosion area" or "flood-related erosion prone area" means a land area adjoining the shore of a lake or other body of water, which due to the composition of the shoreline or bank and high water levels or wind-driven currents, is likely to suffer flood-related erosion damage.
- (30) "Flood-related erosion area management" means the operation of an overall program of corrective and preventive measures for reducing flood-related erosion damage, including but not limited to emergency preparedness plans, flood-related erosion control works and floodplain management regulations.
- (31) "Floodway" means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than a designated height.
- (32) "Freeboard" means a factor of safety usually expressed in feet above a flood level for purposes of floodplain management. "Freeboard" tends to compensate for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as wave action, blockage of bridge or culvert openings, and the hydrological effect of urbanization of the watershed.
- (33) "Functionally dependent use" means a use which cannot perform its intended purpose unless it is located or carried out in close proximity to

- water. The term includes only docking facilities, port facilities that are necessary for the loading and unloading of cargo or passengers, and ship building and ship repair facilities, but does not include long-term storage or related manufacturing facilities.
- (34) "Highest adjacent grade" means the highest natural elevation of the ground surface, prior to construction, adjacent to the proposed walls of a structure.
 - (35) "Historic structure" means any structure that is:
 - (a) Listed individually in the National Register of Historic Places (a listing maintained by the U.S. Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
 - (b) Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district;
 - (c) Individually listed on the Tennessee inventory of historic places and determined as eligible by states with historic preservation programs which have been approved by the Secretary of the Interior; or
 - (d) Individually listed on the City of Shelbyville, Tennessee inventory of historic places and determined as eligible by communities with historic preservation programs that have been certified either:
 - (i) By the approved Tennessee program as determined by the Secretary of the Interior; or
 - (ii) Directly by the Secretary of the Interior.
- (36) "Levee" means a man-made structure, usually an earthen embankment, designed and constructed in accordance with sound engineering practices to contain, control or divert the flow of water so as to provide protection from temporary flooding.
- (37) "Levee system" means a flood protection system which consists of a levee, or levees, and associated structures, such as closure and drainage devices, which are constructed and operated in accordance with sound engineering practices.
- (38) "Lowest floor" means the lowest floor of the lowest enclosed area, including a basement. An unfinished or flood resistant enclosure used solely for parking of vehicles, building access or storage in an area other than a basement area is not considered a building's lowest floor; provided, that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements of this ordinance.
- (39) "Manufactured home" means a structure, transportable in one or more sections, which is built on a permanent chassis and designed for use with or without a permanent foundation when attached to the required utilities. The term "manufactured home" does not include a "recreational vehicle."

- (40) "Manufactured home park or subdivision" means a parcel (or contiguous parcels) of land divided into two (2) or more manufactured home lots for rent or sale.
- (41) "Map" means the Flood Hazard Boundary Map (FHBM) or the Flood Insurance Rate Map (FIRM) for a community issued by FEMA.
- (42) "Mean Sea Level" means the average height of the sea for all stages of the tide. It is used as a reference for establishing various elevations within the floodplain. For the purposes of this ordinance, the term is synonymous with the National Geodetic Vertical Datum (NGVD) of 1929, the North American Vertical Datum (NAVD) of 1988, or other datum, to which base flood elevations shown on a community's flood insurance rate map are referenced.
- (43) "National Geodetic Vertical Datum (NGVD)" means, as corrected in 1929, a vertical control used as a reference for establishing varying elevations within the floodplain.
- (44) "New construction" means any structure for which the "start of construction" commenced on or after the effective date of the initial floodplain management ordinance and includes any subsequent improvements to such structure.
- (45) "New manufactured home park or subdivision" means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed on or after the effective date of this ordinance or the effective date of the initial floodplain management ordinance and includes any subsequent improvements to such structure.
- (45) "North American Vertical Datum (NAVD)" means, as corrected in 1988, a vertical control used as a reference for establishing varying elevations within the floodplain.
 - (46) "100-year flood" see "base flood."
- (47) "Person" includes any individual or group of individuals, corporation, partnership, association, or any other entity, including state and local governments and agencies.
- (48) "Reasonably safe from flooding" means base flood waters will not inundate the land or damage structures to be removed from the special flood hazard area and that any subsurface waters related to the base flood will not damage existing or proposed structures.
 - (49) "Recreational vehicle" means a vehicle which is:
 - (a) Built on a single chassis;
 - (b) Four hundred (400) square feet or less when measured at the largest horizontal projection;
 - (c) Designed to be self-propelled or permanently towable by a light duty truck;

- (d) Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.
- (50) "Regulatory floodway" means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than a designated height.
- (51) "Riverine" means relating to, formed by, or resembling a river (including tributaries), stream, brook, etc.
- (52) "Special flood hazard area" is the land in the floodplain within a community subject to a one percent (1%) or greater chance of flooding in any given year. The area may be designated as Zone A on the FHBM. After detailed ratemaking has been completed in preparation for publication of the FIRM, Zone A usually is refined into Zones A, AO, AH, A1-30, AE or A99.
- (53) "Special hazard area" means an area having special flood, mudslide (i.e., mudflow) and/or flood-related erosion hazards, and shown on an FHBM or FIRM as Zone A, AO, A1-30, AE, A99, or AH.
- "Start of construction" includes substantial improvement, and (54)means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, or other improvement was within one hundred eighty (180) days of the permit date. The actual start means either the first placement of permanent construction of a structure (including a manufactured home) on a site, such as the pouring of slabs or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; and include the placement of a manufactured home on a foundation. Permanent construction does not include initial land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds, not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.
- (55) "State coordinating agency" the Tennessee Department of Economic and Community Development, as designated by the Governor of the State of Tennessee at the request of FEMA to assist in the implementation of the NFIP for the state.
- (56) "Structure" for purposes of this ordinance, means a walled and roofed building, including a gas or liquid storage tank that is principally above ground, as well as a manufactured home.
- (57) "Substantial damage" means damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damaged

condition would equal or exceed fifty percent (50%) of the market value of the structure before the damage occurred.

(58) "Substantial improvement" means any reconstruction, rehabilitation, addition, alteration or other improvement of a structure in which the cost equals or exceeds fifty percent (50%) of the market value of the structure before the "start of construction" of the initial improvement. This term includes structures which have incurred "substantial damage", regardless of the actual repair work performed. The market value of the structure should be (1) the appraised value of the structure prior to the start of the initial improvement, or (2) in the case of substantial damage, the value of the structure prior to the damage occurring.

The term does not, however, include either: (1) Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been pre-identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions and not solely triggered by an improvement or repair project or; (2) Any alteration of a "historic structure," provided that the alteration will not preclude the structure's continued designation as a "historic structure."

- (59) "Substantially improved existing manufactured home parks or subdivisions" is where the repair, reconstruction, rehabilitation or improvement of the streets, utilities and pads equals or exceeds fifty percent (50%) of the value of the streets, utilities and pads before the repair, reconstruction or improvement commenced.
- (60) "Variance" is a grant of relief from the requirements of this ordinance.
- (61) "Violation" means the failure of a structure or other development to be fully compliant with the community's floodplain management regulations. A structure or other development without the elevation certificate, other certification, or other evidence of compliance required in this ordinance is presumed to be in violation until such time as that documentation is provided.
- (62) "Water surface elevation" means the height, in relation to the National Geodetic Vertical Datum (NGVD) of 1929, the North American Vertical Datum (NAVD) of 1988, or other datum, where specified, of floods of various magnitudes and frequencies in the floodplains of riverine areas. (as added by Ord. #2014-932, Jan. 2014)
- 11-403. <u>General provisions</u>. (1) <u>Application</u>. This ordinance shall apply to all areas within the incorporated area of the City of Shelbyville, Tennessee.
- (2) <u>Basis for establishing the areas of special flood hazard</u>. The areas of special flood hazard identified on the City of Shelbyville, Tennessee, as identified by FEMA, and in its Flood Insurance Study (FIS) and Flood Insurance Rate Map (FIRM), Community Panel Numbers:

47003C0189E; 47003C0190E; 47003C0200E; 47003C0282E; 47003C0301E; 47003C0302E; 47003C0303E; 47003C0304E; 47003C0306E; 47003C0310E

dated 08/02/2007, along with all supporting technical data, are adopted by reference and declared to be a part of this ordinance.

- (3) Requirement for development permit. A development permit shall be required in conformity with this ordinance prior to the commencement of any development activities.
- (4) <u>Compliance</u>. No land, structure or use shall hereafter be located, extended, converted or structurally altered without full compliance with the terms of this ordinance and other applicable regulations.
- (5) <u>Abrogation and greater restrictions</u>. This ordinance is not intended to repeal, abrogate, or impair any existing easements, covenants or deed restrictions. However, where this ordinance conflicts or overlaps with another regulatory instrument, whichever imposes the more stringent restrictions shall prevail.
- (6) <u>Interpretation</u>. In the interpretation and application of this ordinance, all provisions shall be:
 - (a) Considered as minimum requirements;
 - (b) Liberally construed in favor of the governing body; and
 - (c) Deemed neither to limit nor repeal any other powers granted under Tennessee statutes.
- (7) Warning and disclaimer of liability. The degree of flood protection required by this ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. Larger floods can and will occur on rare occasions. Flood heights may be increased by man-made or natural causes. This ordinance does not imply that land outside the areas of special flood hazard or uses permitted within such areas will be free from flooding or flood damages. This ordinance shall not create liability on the part of the City of Shelbyville, Tennessee or by any officer or employee thereof for any flood damages that result from reliance on this ordinance or any administrative decision lawfully made hereunder.
- (8) Penalties for violation. Violation of the provisions of this ordinance or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance shall constitute a misdemeanor punishable as other misdemeanors as provided by law. Any person who violates this ordinance or fails to comply with any of its requirements shall, upon adjudication therefore, be fined as prescribed by Tennessee statutes, and in addition, shall pay all costs and expenses involved in the case. Each day such violation continues shall be considered a separate offense. Nothing herein contained shall prevent the City of Shelbyville, Tennessee from taking such other lawful actions to prevent or remedy any violation. (as added by Ord. #2014-932, Jan. 2014)

- 11-404. <u>Administration</u>. (1) <u>Designation of ordinance administrator</u>. The codes director is hereby appointed as the administrator to implement the provisions of this ordinance.
- (2) <u>Permit procedures</u>. Application for a development permit shall be made to the administrator on forms furnished by the community prior to any development activities. The development permit may include, but is not limited to the following: plans in duplicate drawn to scale and showing the nature, location, dimensions, and elevations of the area in question; existing or proposed structures, earthen fill placement, storage of materials or equipment, and drainage facilities. Specifically, the following information is required:
 - (a) Application stage. (i) Elevation in relation to mean sea level of the proposed lowest floor, including basement, of all buildings where base flood elevations are available, or to certain height above the highest adjacent grade when applicable under this ordinance.
 - (ii) Elevation in relation to mean sea level to which any non-residential building will be floodproofed where base flood elevations are available, or to certain height above the highest adjacent grade when applicable under this ordinance.
 - (iii) A FEMA Floodproofing Certificate from a Tennessee registered professional engineer or architect that the proposed non-residential floodproofed building will meet the floodproofing criteria in § 11-405(1) and (2).
 - (iv) Description of the extent to which any watercourse will be altered or relocated as a result of proposed development.
 - (b) Construction stage. Within AE Zones, where base flood elevation data is available, any lowest floor certification made relative to mean sea level shall be prepared by or under the direct supervision of, a Tennessee registered land surveyor and certified by same. The administrator shall record the elevation of the lowest floor on the development permit. When flood proofing is utilized for a non-residential building, said certification shall be prepared by, or under the direct supervision of, a Tennessee registered professional engineer or architect and certified by same.

Within approximate A Zones, where base flood elevation data is not available, the elevation of the lowest floor shall be determined as the measurement of the lowest floor of the building relative to the highest adjacent grade. The administrator shall record the elevation of the lowest floor on the development permit. When flood proofing is utilized for a non-residential building, said certification shall be prepared by, or under the direct supervision of, a Tennessee registered professional engineer or architect and certified by same.

For all new construction and substantial improvements, the permit holder shall provide to the administrator an as-built certification of the lowest floor elevation or flood proofing level upon the completion of the lowest floor or flood proofing.

Any work undertaken prior to submission of the certification shall be at the permit holder's risk. The administrator shall review the above-referenced certification data. Deficiencies detected by such review shall be corrected by the permit holder immediately and prior to further work being allowed to proceed. Failure to submit the certification or failure to make said corrections required hereby, shall be cause to issue a stop-work order for the project.

- (3) <u>Duties and responsibilities of the administrator</u>. Duties of the administrator shall include, but not be limited to, the following:
 - (a) Review all development permits to assure that the permit requirements of this ordinance have been satisfied, and that proposed building sites will be reasonably safe from flooding.
 - (b) Review proposed development to assure that all necessary permits have been received from those governmental agencies from which approval is required by federal or state law, including section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334.
 - (c) Notify adjacent communities and the Tennessee Department of Economic and Community Development, Local Planning Assistance Office, prior to any alteration or relocation of a watercourse and submit evidence of such notification to FEMA.
 - (d) For any altered or relocated watercourse, submit engineering data/analysis within six (6) months to FEMA to ensure accuracy of community FIRM's through the letter of map revision process.
 - (e) Assure that the flood carrying capacity within an altered or relocated portion of any watercourse is maintained.
 - (f) Record the elevation, in relation to mean sea level or the highest adjacent grade, where applicable, of the lowest floor (including basement) of all new and substantially improved buildings, in accordance with § 11-404(2).
 - (g) Record the actual elevation, in relation to mean sea level or the highest adjacent grade, where applicable to which the new and substantially improved buildings have been flood proofed, in accordance with § 11-404(2).
 - (h) When flood proofing is utilized for a nonresidential structure, obtain certification of design criteria from a Tennessee registered professional engineer or architect, in accordance with § 11-404(2).
 - (i) Where interpretation is needed as to the exact location of boundaries of the areas of special flood hazard (for example, where there appears to be a conflict between a mapped boundary and actual field conditions), make the necessary interpretation. Any person contesting the

location of the boundary shall be given a reasonable opportunity to appeal the interpretation as provided in this ordinance.

- (j) When base flood elevation data and floodway data have not been provided by FEMA, obtain, review, and reasonably utilize any base flood elevation and floodway data available from a federal, state, or other sources, including data developed as a result of these regulations, as criteria for requiring that new construction, substantial improvements, or other development in Zone A on the City of Shelbyville, Tennessee FIRM meet the requirements of this ordinance.
- (k) Maintain all records pertaining to the provisions of this ordinance in the office of the administrator and shall be open for public inspection. Permits issued under the provisions of this ordinance shall be maintained in a separate file or marked for expedited retrieval within combined files. (as added by Ord. #2014-932, Jan. 2014)
- 11-405. <u>Provisions for flood hazard reduction</u>. (1) <u>General standards</u>. In all areas of special flood hazard, the following provisions are required:
 - (a) New construction and substantial improvements shall be anchored to prevent flotation, collapse and lateral movement of the structure;
 - (b) Manufactured homes shall be installed using methods and practices that minimize flood damage. They must be elevated and anchored to prevent flotation, collapse and lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors. This requirement is in addition to applicable State of Tennessee and local anchoring requirements for resisting wind forces.
 - (c) New construction and substantial improvements shall be constructed with materials and utility equipment resistant to flood damage;
 - (d) New construction and substantial improvements shall be constructed by methods and practices that minimize flood damage;
 - (e) All electrical, heating, ventilation, plumbing, air conditioning equipment, and other service facilities shall be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding;
 - (f) New and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the system;
 - (g) New and replacement sanitary sewage systems shall be designed to minimze or eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters;

- (h) On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding;
- (i) Any alteration, repair, reconstruction or improvements to a building that is in compliance with the provisions of this ordinance, shall meet the requirements of "new construction" as contained in this ordinance;
- (j) Any alteration, repair, reconstruction or improvements to a building that is not in compliance with the provision of this ordinance, shall be undertaken only if said non-conformity is not further extended or replaced;
- (k) All new construction and substantial improvement proposals shall provide copies of all necessary federal and state permits, including section 404 of the Federal Water Pollution Control Act amendments of 1972, 33 U.S.C. 1334;
- (l) All subdivision proposals and other proposed new development proposals shall meet the standards of § 11-405(2);
- (m) When proposed new construction and substantial improvements are partially located in an area of special flood hazard, the entire structure shall meet the standards for new construction;
- (n) When proposed new construction and substantial improvements are located in multiple flood hazard risk zones or in a flood hazard risk zone with multiple base flood elevations, the entire structure shall meet the standards for the most hazardous flood hazard risk zone and the highest base flood elevation.
- (2) <u>Specific standards</u>. In all areas of special flood hazard, the following provisions, in addition to those set forth in § 11-405(1) are required:
 - (a) Residential Structures. In AE Zones where base flood elevation data is available, new construction and substantial improvement of any residential building (or manufactured home) shall have the lowest floor, including basement, elevated to no lower than one foot (1') above the base flood elevation. Should solid foundation perimeter walls be used to elevate a structure, openings sufficient to facilitate equalization of flood hydrostatic forces on both sides of exterior walls shall be provided in accordance with the standards of this section: "Enclosures."

Within approximate A Zones where base flood elevations have not been established and where alternative data is not available, the administrator shall require the lowest floor of a building to be elevated to a level of at least three feet (3') above the highest adjacent grade (as defined in § 11-402). Should solid foundation perimeter walls be used to elevate a structure, openings sufficient to facilitate equalization of flood hydrostatic forces on both sides of exterior walls shall be provided in accordance with the standards of this section: "Enclosures."

(b) Non-residential structures. In AE Zones, where base flood elevation data is available, new construction and substantial improvement of any commercial, industrial, or non-residential building, shall have the lowest floor, including basement, elevated or flood proofed to no lower than one foot (1') above the level of the base flood elevation. Should solid foundation perimeter walls be used to elevate a structure, openings sufficient to facilitate equalization of flood hydrostatic forces on both sides of exterior walls shall be provided in accordance with the standards of this section: "Enclosures."

In approximate A Zones, where base flood elevations have not been established and where alternative data is not available, new construction and substantial improvement of any commercial, industrial, or non-residential building, shall have the lowest floor, including basement, elevated or flood proofed to no lower than three feet (3') above the highest adjacent grade (as defined in § 11-402). Should solid foundation perimeter walls be used to elevate a structure, openings sufficient to facilitate equalization of flood hydrostatic forces on both sides of exterior walls shall be provided in accordance with the standards of this section: "Enclosures."

Non-residential buildings located in all A Zones may be flood proofed, in lieu of being elevated, provided that all areas of the building below the required elevation are watertight, with walls substantially impermeable to the passage of water, and are built with structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy. A Tennessee registered professional engineer or architect shall certify that the design and methods of construction are in accordance with accepted standards of practice for meeting the provisions above, and shall provide such certification to the administrator as set forth in § 11-404(2).

- (c) Enclosures. All new construction and substantial improvements that include fully enclosed areas formed by foundation and other exterior walls below the lowest floor that are subject to flooding, shall be designed to preclude finished living space and designed to allow for the entry and exit of flood waters to automatically equalize hydrostatic flood forces on exterior walls.
 - (i) Designs for complying with this requirement must either be certified by a Tennessee professional engineer or architect or meet or exceed the following minimum criteria.
 - (A) Provide a minimum of two (2) openings having a total net area of not less than one (1) square inch for every square foot of enclosed area subject to flooding;
 - (B) The bottom of all openings shall be no higher than one foot (1') above the finished grade;

- (C) Openings may be equipped with screens, louvers, valves or other coverings or devices provided they permit the automatic flow of floodwaters in both directions.
- (ii) The enclosed area shall be the minimum necessary to allow for parking of vehicles, storage or building access.
- (iii) The interior portion of such enclosed area shall not be finished or partitioned into separate rooms in such a way as to impede the movement of floodwaters and all such partitions shall comply with the provisions of § 11-405(2).
- (d) Standards for manufactured homes and recreational vehicles. (i) All manufactured homes placed, or substantially improved, on:
 - (A) Individual lots or parcels;
 - (B) In expansions to existing manufactured home parks or subdivisions; or
 - (C) In new or substantially improved manufactured home parks or subdivisions, must meet all the requirements of new construction.
- (ii) All manufactured homes placed or substantially improved in an existing manufactured home park or subdivision must be elevated so that either:
 - (A) In AE Zones, with base flood elevations, the lowest floor of the manufactured home is elevated on a permanent foundation to no lower than one foot (1') above the level of the base flood elevation; or
 - (B) In approximate A Zones, without base flood elevations, the manufactured home chassis is elevated and supported by reinforced piers (or other foundation elements of at least equivalent strength) that are at least three feet (3') in height above the highest adjacent grade (as defined in § 11-402).
- (iii) Any manufactured home, which has incurred "substantial damage" as the result of a flood, must meet the standards of § 11-405(1) and (2).
- (iv) All manufactured homes must be securely anchored to an adequately anchored foundation system to resist flotation, collapse and lateral movement.
- (v) All recreational vehicles placed in an identified special flood hazard area must either:
 - (A) Be on the site for fewer than one hundred eighty (180) consecutive days;
 - (B) Be fully licensed and ready for highway use (a recreational vehicle is ready for highway use if it is licensed, on its wheels or jacking system, attached to the site only by

quick disconnect type utilities and security devices, and has no permanently attached structures or additions); or

- (C) The recreational vehicle must meet all the requirements for new construction.
- (e) Standards for subdivision and other proposed new development proposals. Subdivisions and other proposed new developments, including manufactured home parks, shall be reviewed to determine whether such proposals will be reasonably safe from flooding.
 - (i) All subdivision and other proposed new development proposals shall be consistent with the need to minimize flood damage.
 - (ii) All subdivision and other proposed new development proposals shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize or eliminate flood damage.
 - (iii) All subdivision and other proposed new development proposals shall have adequate drainage provided to reduce exposure to flood hazards.
 - (iv) In all approximate A Zones require that all new subdivision proposals and other proposed developments (including proposals for manufactured home parks and subdivisions) greater than fifty (50) lots or five (5) acres, whichever is the lesser, include within such proposals base flood elevation (see § 11-405(5)).
- (3) Standards for special flood hazard areas with established base flood elevations and with floodways designated. Located within the special flood hazard areas established in § 11-403(2), are areas designated as floodways. A floodway may be an extremely hazardous area due to the velocity of floodwaters, debris or erosion potential. In addition, the area must remain free of encroachment in order to allow for the discharge of the base flood without increased flood heights and velocities. Therefore, the following provisions shall apply:
 - (a) Encroachments are prohibited, including earthen fill material, new construction, substantial improvements or other development within the regulatory floodway. Development may be permitted however, provided it is demonstrated through hydrologic and hydraulic analyses performed in accordance with standard engineering practices that the cumulative effect of the proposed encroachments or new development shall not result in any increase in the water surface elevation of the base flood elevation, velocities, or floodway widths during the occurrence of a base flood discharge at any point within the community. A Tennessee registered professional engineer must provide supporting technical data, using the same methodologies as in the effective Flood Insurance Study for the City of Shelbyville, Tennessee and certification, thereof.

- (b) New construction and substantial improvements of buildings, where permitted, shall comply with all applicable flood hazard reduction provisions of § 11-405(1) and (2).
- (4) <u>Standards for areas of special flood hazard Zones AE with established base flood elevation but without floodways designated</u>. Located within the special flood hazard areas established in § 11-403(2), where streams exist with base flood data provided but where no floodways have been designated (Zones AE), the following provisions apply:
 - (a) No encroachments, including fill material, new construction and substantial improvements shall be located within areas of special flood hazard, unless certification by a Tennessee registered professional engineer is provided demonstrating that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot (1') at any point within the community. The engineering certification should be supported by technical data that conforms to standard hydraulic engineering principles.
 - (b) New construction and substantial improvements of buildings, where permitted, shall comply with all applicable flood hazard reduction provisions of § 11-405(1) and (2).
- (5) <u>Standards for streams without established base flood elevations and floodways (A Zones)</u>. Located within the special flood hazard areas established in § 11-403(2), where streams exist, but no base flood data has been provided and where a floodway has not been delineated, the following provisions shall apply:
 - (a) The administrator shall obtain, review, and reasonably utilize any base flood elevation and floodway data available from any federal, state, or other sources, including data developed as a result of these regulations (see (b) below), as criteria for requiring that new construction, substantial improvements, or other development in approximate A Zones meet the requirements of § 11-405(1) and (2).
 - (b) Require that all new subdivision proposals and other proposed developments (including proposals for manufactured home parks and subdivisions) greater than fifty (50) lots or five (5) acres, whichever is the lesser, include within such proposals base flood elevation data.
 - (c) Within approximate A Zones, where base flood elevations have not been established and where such data is not available from other sources, require the lowest floor of a building to be elevated or flood proofed to a level of at least three feet (3') above the highest adjacent grade (as defined in § 11-402). All applicable data including elevations or flood proofing certifications shall be recorded as set forth in § 11-404(2). Openings sufficient to facilitate automatic equalization of hydrostatic

flood forces on exterior walls shall be provided in accordance with the standards of § 11-405(2).

- (d) Within approximate A Zones, where base flood elevations have not been established and where such data is not available from other sources, no encroachments, including structures or fill material, shall be located within an area equal to the width of the stream or twenty feet (20') whichever is greater, measured from the top of the stream bank, unless certification by a Tennessee registered professional engineer is provided demonstrating that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot (1') at any point within the City of Shelbyville, Tennessee. The engineering certification should be supported by technical data that conforms to standard hydraulic engineering principles.
- (e) New construction and substantial improvements of buildings, where permitted, shall comply with all applicable flood hazard reduction provisions of § 11-405(1) and (2). Within approximate A Zones, require that those subsections of § 11-405(2) dealing with the alteration or relocation of a watercourse, assuring watercourse carrying capacities are maintained and manufactured homes provisions are complied with as required.
- (6) Standards for areas of shallow flooding (AO and AH Zones). Located within the special flood hazard areas established in § 11-403(2), are areas designated as shallow flooding areas. These areas have special flood hazards associated with base flood depths of one to three feet (1' to 3') where a clearly defined channel does not exist and where the path of flooding is unpredictable and indeterminate; therefore, the following provisions, in addition to those set forth in § 11-405(1) and (2) apply:
 - (a) All new construction and substantial improvements of residential and non-residential buildings shall have the lowest floor, including basement, elevated to at least one foot (1') above as many feet as the depth number specified on the FIRM's, in feet, above the highest adjacent grade. If no flood depth number is specified on the FIRM, the lowest floor, including basement, shall be elevated to at least three feet (3') above the highest adjacent grade. Openings sufficient to facilitate automatic equalization of hydrostatic flood forces on exterior walls shall be provided in accordance with standards of § 11-405(2).
 - (b) All new construction and substantial improvements of non-residential buildings may be flood proofed in lieu of elevation. The structure together with attendant utility and sanitary facilities must be flood proofed and designed watertight to be completely flood proofed to at least one foot (1') above the flood depth number specified on the FIRM, with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and

hydrodynamic loads and the effects of buoyancy. If no depth number is specified on the FIRM, the structure shall be flood proofed to at least three feet (3') above the highest adjacent grade. A Tennessee registered professional engineer or architect shall certify that the design and methods of construction are in accordance with accepted standards of practice for meeting the provisions of this ordinance and shall provide such certification to the administrator as set forth above and as required in accordance with § 11-404(2).

- (c) Adequate drainage paths shall be provided around slopes to guide floodwaters around and away from proposed structures.
- (7) <u>Standards for areas protected by flood protection system (A-99 Zones)</u>. Located within the areas of special flood hazard established in § 11-403(2), are areas of the 100-year floodplain protected by a flood protection system but where base flood elevations have not been determined. Within these areas (A-99 Zones) all provisions of §§ 11-404 and 11-405 shall apply.
- (8) <u>Standards for unmapped streams</u>. Located within the City of Shelbyville, Tennessee, are unmapped streams where areas of special flood hazard are neither indicated nor identified. Adjacent to such streams, the following provisions shall apply:
 - (a) No encroachments including fill material or other development including structures shall be located within an area of at least equal to twice the width of the stream, measured from the top of each stream bank, unless certification by a Tennessee registered professional engineer is provided demonstrating that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot (1') at any point within the locality.
 - (b) When a new flood hazard risk zone, and base flood elevation and floodway data is available, new construction and substantial improvements shall meet the standards established in accordance with §§ 11-404 and 11-405. (as added by Ord. #2014-932, Jan. 2014)

11-406. <u>Variance procedures</u>. (1) <u>Municipal board of zoning appeals</u>.

- (a) Authority. The City of Shelbyville, Tennessee Municipal Board of Zoning Appeals shall hear and decide appeals and requests for variances from the requirements of this ordinance.
- (b) Procedure. Meetings of the municipal board of zoning appeals shall be held at such times, as the board shall determine. All meetings of the municipal board of zoning appeals shall be open to the public. The municipal board of zoning appeals shall adopt rules of procedure and shall keep records of applications and actions thereof, which shall be a public record. Compensation of the members of the municipal board of zoning appeals shall be set by the legislative body.

- Appeals; how taken. An appeal to the municipal board of zoning appeals may be taken by any person, firm or corporation aggrieved or by any governmental officer, department, or bureau affected by any decision of the administrator based in whole or in part upon the provisions of this ordinance. Such appeal shall be taken by filing with the municipal board of zoning appeals a notice of appeal, specifying the grounds thereof. In all cases where an appeal is made by a property owner or other interested party, a fee of (amount) dollars for the cost of publishing a notice of such hearings shall be paid by the appellant. The administrator shall transmit to the municipal board of zoning appeals all papers constituting the record upon which the appeal action was taken. The municipal board of zoning appeals shall fix a reasonable time for the hearing of the appeal, give public notice thereof, as well as due notice to parties in interest and decide the same within a reasonable time which shall not be more than (number of) days from the date of the hearing. At the hearing, any person or party may appear and be heard in person or by agent or by attorney.
- (d) Powers. The municipal board of zoning appeals shall have the following powers:
 - (i) Administrative review. To hear and decide appeals where it is alleged by the applicant that there is error in any order, requirement, permit, decision, determination, or refusal made by the administrator or other administrative official in carrying out or enforcement of any provisions of this ordinance.
 - (ii) Variance procedures. In the case of a request for a variance the following shall apply:
 - (A) The City of Shelbyville, Tennessee Municipal Board of Zoning Appeals shall hear and decide appeals and requests for variances from the requirements of this ordinance.
 - (B) Variances may be issued for the repair or rehabilitation of historic structures as defined herein, upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and the variance is the minimum necessary deviation from the requirements of this ordinance to preserve the historic character and design of the structure.
 - (C) In passing upon such applications, the municipal board of zoning appeals shall consider all technical evaluations, all relevant factors, all standards specified in other sections of this ordinance; and
 - (1) The danger that materials may be swept onto other property to the injury of others;

- (2) The danger to life and property due to flooding or erosion;
- (3) The susceptibility of the proposed facility and its contents to flood damage;
- (4) The importance of the services provided by the proposed facility to the community;
- (5) The necessity of the facility to a waterfront location, in the case of a functionally dependent use;
- (6) The availability of alternative locations, not subject to flooding or erosion damage, for the proposed use;
- (7) The relationship of the proposed use to the comprehensive plan and floodplain management program for that area;
- (8) The safety of access to the property in times of flood for ordinary and emergency vehicles;
- (9) The expected heights, velocity, duration, rate of rise and sediment transport of the flood waters and the effects of wave action, if applicable, expected at the site;
- (10) The costs of providing governmental services during and after flood conditions including maintenance and repair of public utilities and facilities such as sewer, gas, electrical, water systems, and streets and bridges.
- (D) Upon consideration of the factors listed above, and the purposes of this ordinance, the municipal board of zoning appeals may attach such conditions to the granting of variances, as it deems necessary to effectuate the purposes of this ordinance.
- (E) Variances shall not be issued within any designated floodway if any increase in flood levels during the base flood discharge would result.
- (2) <u>Conditions for variances</u>. (a) Variances shall be issued upon a determination that the variance is the minimum relief necessary, considering the flood hazard and the factors listed in § 11-406(1).
- (b) Variances shall only be issued upon: a showing of good and sufficient cause, a determination that failure to grant the variance would result in exceptional hardship; or a determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisance, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.

- (c) Any applicant to whom a variance is granted shall be given written notice that the issuance of a variance to construct a structure below the base flood elevation will result in increased premium rates for flood insurance (as high as twenty-five dollars (\$25.00) for one hundred dollars (\$100.00)) coverage, and that such construction below the base flood elevation increases risks to life and property.
- (d) The administrator shall maintain the records of all appeal actions and report any variances to FEMA upon request. (as added by Ord. #2014-932, Jan. 2014)
- 11-407. <u>Legal status provisions</u>. (1) <u>Conflict with other ordinances</u>. In case of conflict between this ordinance or any part thereof, and the whole or part of any existing or future ordinance of the City of Shelbyville, Tennessee, the most restrictive shall in all cases apply.
- (2) <u>Severability</u>. If any section, clause, provision, or portion of this ordinance shall be held to be invalid or unconstitutional by any court of competent jurisdiction, such holding shall not affect any other section, clause, provision, or portion of this ordinance which is not of itself invalid or unconstitutional. (as added by Ord. #2014-932, Jan. 2014)